



US009119931B2

(12) **United States Patent**
D'Souza et al.

(10) **Patent No.:** **US 9,119,931 B2**
(45) **Date of Patent:** ***Sep. 1, 2015**

(54) **MASK SYSTEM**

(71) Applicant: **ResMed Limited**, Bella Vista, New South Wales (AU)

(72) Inventors: **Errol Savio Alex D'Souza**, Sydney (AU); **Matthew Eves**, Sydney (AU); **David James Lockwood**, Gosford (AU); **Zoran Valcic**, Sydney (AU); **Jamie Graeme Wehbeh**, Sydney (AU)

(73) Assignee: **ResMed Limited**, Bella Vista (AU)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/447,673**

(22) Filed: **Jul. 31, 2014**

(65) **Prior Publication Data**

US 2014/0338672 A1 Nov. 20, 2014

Related U.S. Application Data

(63) Continuation of application No. 13/964,280, filed on Aug. 12, 2013, which is a continuation of application No. 13/745,077, filed on Jan. 18, 2013, now Pat. No. 8,528,561, which is a continuation of application No.

(Continued)

(51) **Int. Cl.**
A62B 18/02 (2006.01)
A61M 16/06 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **A61M 16/0683** (2013.01); **A61M 16/0057** (2013.01); **A61M 16/0066** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC A61M 16/06; A61M 16/0605; A61M 16/0611; A61M 16/0616; A61M 16/0683
USPC 128/205.25, 206.21, 206.24, 206.28, 128/207.11

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

364,394 A 6/1887 Bright
428,592 A 5/1890 Chapman

(Continued)

FOREIGN PATENT DOCUMENTS

AU 91/77110 11/1991
AU 94/64816 12/1994

(Continued)

OTHER PUBLICATIONS

Innovation Patent Examination Report No. 2 issued Aug. 8, 2014 in Australian Application No. 2014100361 (5 pages).

(Continued)


Primary Examiner — Kristen Matter

(74) *Attorney, Agent, or Firm* — Nixon & Vanderhye P.C.

(57) **ABSTRACT**

A mask system has a shroud module with headgear connectors adapted to removably attach to respective headgear straps of headgear; and a cushion module, including a frame defining a breathing chamber; and a cushion to form a seal with the patient's face in a nasal bridge region, a cheek region and a lower lip/chin region of the patient's face. The cushion is constructed of a first, relatively soft, elastomeric material and the frame is constructed of a second material that is more rigid than the cushion, and a nasal bridge portion of the cushion includes one or more folds to provide in use a higher level of adaptability or flexibility to the nasal bridge region of the cushion module relative to another region of the cushion module. The shroud module and the cushion module are configured to be removably coupleable to one another.

79 Claims, 81 Drawing Sheets



Fisher & Paykel Ex. 1501
IPR Petition - USP 9,119,931

Related U.S. Application Data

- 12/736,024, filed as application No. PCT/AU2009/000241 on Feb. 27, 2009, now Pat. No. 8,550,084.
- (60) Provisional application No. 61/064,406, filed on Mar. 4, 2008, provisional application No. 61/071,893, filed on May 23, 2008, provisional application No. 61/136,617, filed on Sep. 19, 2008.
- (51) **Int. Cl.**
A61M 16/00 (2006.01)
A61M 16/08 (2006.01)
A61M 16/20 (2006.01)
- (52) **U.S. Cl.**
 CPC *A61M16/06* (2013.01); *A61M 16/0611* (2014.02); *A61M 16/0616* (2014.02); *A61M 16/0622* (2014.02); *A61M 16/0694* (2014.02); *A61M 16/0816* (2013.01); *A61M 16/0875* (2013.01); *A61M 16/20* (2013.01); *A61M 2016/0661* (2013.01)

References Cited

U.S. PATENT DOCUMENTS

- | | | | | | | | |
|-----------|---|---------|------------------|-----------|---|---------|-----------------------|
| 443,191 | A | 12/1890 | Illing | 2,706,983 | A | 4/1955 | Matheson et al. |
| 781,516 | A | 1/1905 | Guthrie, Jr. | 2,749,910 | A | 6/1956 | Faulconer, Jr. |
| 812,706 | A | 2/1906 | Warbasse | RE24,193 | E | 8/1956 | Emerson |
| 1,081,745 | A | 12/1913 | Johnston et al. | 2,820,651 | A | 1/1958 | Phillips |
| 1,125,542 | A | 1/1915 | Humphries | 2,837,090 | A | 6/1958 | Bloom et al. |
| 1,176,886 | A | 3/1916 | Ermold | 2,868,196 | A | 1/1959 | Stampe |
| 1,192,186 | A | 7/1916 | Greene | 2,875,757 | A | 3/1959 | Galleher, Jr. |
| 1,206,045 | A | 11/1916 | Smith | 2,875,759 | A | 3/1959 | Galleher, Jr. |
| 1,229,050 | A | 6/1917 | Donald | 2,881,444 | A | 4/1959 | Fresh et al. |
| 1,282,527 | A | 10/1918 | Bidonde | 2,882,895 | A | 4/1959 | Galeazzi |
| 1,362,766 | A | 12/1920 | McGargill | 2,902,033 | A | 9/1959 | Galleher, Jr. |
| 1,445,010 | A | 2/1923 | Feinberg | 2,917,045 | A | 12/1959 | Schildknecht et al. |
| 1,502,450 | A | 7/1924 | Wood | 2,931,356 | A | 4/1960 | Schwarz |
| 1,610,793 | A | 12/1926 | Kaufman | D188,084 | S | 5/1960 | Garellick |
| 1,632,449 | A | 6/1927 | McKesson | 2,939,458 | A | 6/1960 | Lundquist |
| 1,653,572 | A | 12/1927 | Jackson | 3,013,556 | A | 12/1961 | Galleher, Jr. |
| 1,710,160 | A | 4/1929 | Gibbs | 3,042,035 | A | 7/1962 | Coanda |
| 1,837,591 | A | 12/1931 | Shindel | 3,117,574 | A | 1/1964 | Replogle |
| 1,873,160 | A | 8/1932 | Sturtevant | 3,182,659 | A | 5/1965 | Blount |
| 1,926,027 | A | 9/1933 | Biggs | 3,189,027 | A | 6/1965 | Bartlett, Jr. |
| 2,011,733 | A | 8/1935 | Shindel | 3,193,624 | A | 7/1965 | Webb et al. |
| 2,104,016 | A | 1/1938 | Biggs | 3,238,943 | A | 3/1966 | Holley |
| 2,123,353 | A | 7/1938 | Catt | 3,288,138 | A | 11/1966 | Sachs |
| 2,127,136 | A | 8/1938 | Pobirs | 3,315,672 | A | 4/1967 | Cunningham et al. |
| 2,130,555 | A | 9/1938 | Malcom | 3,315,674 | A | 4/1967 | Bloom et al. |
| 2,133,699 | A | 10/1938 | Heidbrink | 3,330,273 | A | 7/1967 | Bennett |
| 2,149,067 | A | 2/1939 | Otero | 3,330,274 | A | 7/1967 | Bennett |
| 2,166,164 | A | 7/1939 | Lehmberg | 3,362,420 | A | 1/1968 | Blackburn et al. |
| 2,245,658 | A | 6/1941 | Erickson | 3,363,833 | A | 1/1968 | Laerdal |
| 2,245,969 | A | 6/1941 | Francisco et al. | 3,545,436 | A | 12/1970 | Holloway |
| 2,248,477 | A | 7/1941 | Lombard | 3,556,122 | A | 1/1971 | Laerdal |
| 2,254,854 | A | 9/1941 | O'Connell | 3,580,051 | A | 5/1971 | Blevins |
| 2,317,608 | A | 4/1943 | Heidbrink | 3,670,726 | A | 6/1972 | Mahon et al. |
| 2,353,643 | A | 7/1944 | Bulbulian | 3,682,171 | A | 8/1972 | Dali et al. |
| 2,371,965 | A | 3/1945 | Lehmberg | 3,700,000 | A | 10/1972 | Hesse et al. |
| 2,376,871 | A | 5/1945 | Fink | 3,720,235 | A | 3/1973 | Schrock |
| 2,382,364 | A | 8/1945 | Yant | 3,725,953 | A | 4/1973 | Johnson et al. |
| 2,415,846 | A | 2/1947 | Randall | 3,739,774 | A | 6/1973 | Gregory |
| 2,428,451 | A | 10/1947 | Emerson | 3,750,333 | A | 8/1973 | Vance |
| 2,433,565 | A | 12/1947 | Korman | 3,752,157 | A | 8/1973 | Malmin |
| 2,438,058 | A | 3/1948 | Kincheloe | 3,754,552 | A | 8/1973 | King |
| 2,473,518 | A | 6/1949 | Garrard et al. | 3,796,216 | A | 3/1974 | Schwarz |
| D156,060 | S | 11/1949 | Wade | 3,799,164 | A | 3/1974 | Rollins |
| D161,337 | S | 12/1950 | Hill | D231,803 | S | 6/1974 | Huddy |
| 2,540,567 | A | 2/1951 | Bennett | 3,830,230 | A | 8/1974 | Chester |
| 2,578,621 | A | 12/1951 | Yant | 3,861,385 | A | 1/1975 | Carden |
| 2,590,006 | A | 3/1952 | Gordon | 3,902,486 | A | 9/1975 | Guichard |
| 2,625,155 | A | 1/1953 | Engelder | 3,905,361 | A | 9/1975 | Hewson et al. |
| 2,641,253 | A | 6/1953 | Engelder | 3,910,261 | A | 10/1975 | Ragsdale et al. |
| 2,693,178 | A | 11/1954 | Gilroy | 3,938,614 | A | 2/1976 | Ahs |
| | | | | 3,972,321 | A | 8/1976 | Proctor |
| | | | | 3,978,854 | A | 9/1976 | Mills, Jr. |
| | | | | 4,006,744 | A | 2/1977 | Steer |
| | | | | 4,062,357 | A | 12/1977 | Laerdal |
| | | | | 4,069,516 | A | 1/1978 | Watkins, Jr. |
| | | | | 4,077,404 | A | 3/1978 | Elam |
| | | | | D248,497 | S | 7/1978 | Slosek |
| | | | | D250,131 | S | 10/1978 | Lewis et al. |
| | | | | 4,120,302 | A | 10/1978 | Ziegler |
| | | | | 4,142,527 | A | 3/1979 | Garcia |
| | | | | 4,153,051 | A | 5/1979 | Shippert |
| | | | | 4,156,426 | A | 5/1979 | Gold |
| | | | | 4,167,185 | A | 9/1979 | Lewis |
| | | | | 4,201,205 | A | 5/1980 | Bartholomew |
| | | | | 4,226,234 | A | 10/1980 | Gunderson |
| | | | | 4,231,363 | A | 11/1980 | Grimes |
| | | | | 4,233,972 | A | 11/1980 | Hauff et al. |
| | | | | 4,239,038 | A | 12/1980 | Holmes |
| | | | | 4,245,632 | A | 1/1981 | Houston |
| | | | | 4,248,218 | A | 2/1981 | Fischer |
| | | | | 4,263,908 | A | 4/1981 | Mizerak |
| | | | | 4,264,743 | A | 4/1981 | Maruyama et al. |
| | | | | 4,265,239 | A | 5/1981 | Fischer, Jr. et al. |
| | | | | 4,266,540 | A | 5/1981 | Panzik et al. |
| | | | | 4,267,845 | A | 5/1981 | Robertson, Jr. et al. |
| | | | | 4,273,124 | A | 6/1981 | Zimmerman |
| | | | | D262,322 | S | 12/1981 | Mizerak |
| | | | | 4,304,229 | A | 12/1981 | Curtin |
| | | | | 4,312,359 | A | 1/1982 | Olson |

(56)

References Cited

U.S. PATENT DOCUMENTS

4,328,797 A	5/1982	Rollins et al.	4,832,017 A	5/1989	Schnoor
4,337,767 A	7/1982	Yahata	4,838,878 A	6/1989	Kalt et al.
4,347,205 A	8/1982	Stewart	4,841,953 A	6/1989	Dodrill
4,354,488 A	10/1982	Bartos	4,848,334 A	7/1989	Bellm
4,367,735 A	1/1983	Dali	4,848,366 A	7/1989	Aita et al.
4,367,816 A	1/1983	Wilkes	4,850,346 A	7/1989	Michel et al.
4,369,284 A	1/1983	Chen	4,856,118 A	8/1989	Sapiejewski
4,402,316 A	9/1983	Gadberry	D304,384 S	10/1989	Derobert
4,406,283 A	9/1983	Bir	4,886,058 A	12/1989	Brostrom et al.
4,412,537 A	11/1983	Tiger	4,899,740 A	2/1990	Napolitano
4,414,973 A	11/1983	Matheson et al.	4,905,683 A	3/1990	Cronjaeger
4,417,575 A	11/1983	Hilton et al.	4,907,584 A	3/1990	McGinnis
4,422,456 A	12/1983	Tiep	4,910,806 A	3/1990	Baker et al.
4,446,576 A	5/1984	Hisataka	4,914,957 A	4/1990	Dougherty
4,449,526 A	5/1984	Elam	4,915,105 A	4/1990	Lee
4,454,880 A	6/1984	Muto et al.	4,915,106 A	4/1990	Aulgur et al.
4,454,881 A	6/1984	Huber et al.	4,919,128 A	4/1990	Kopala et al.
4,455,675 A	6/1984	Bose et al.	4,919,654 A	4/1990	Kalt
4,458,679 A	7/1984	Ward	4,938,210 A	7/1990	Shene
4,467,799 A	8/1984	Steinberg	4,938,212 A	7/1990	Snook et al.
4,493,614 A	1/1985	Chu et al.	4,941,476 A	7/1990	Fisher
4,522,639 A	6/1985	Ansite et al.	4,944,310 A	7/1990	Sullivan
4,548,200 A	10/1985	Wapner	4,945,907 A	8/1990	Tayebi
4,549,542 A	10/1985	Chein	4,947,860 A	8/1990	Fisher
4,558,710 A	12/1985	Eichler	D310,431 S	9/1990	Bellm
4,572,323 A	2/1986	Randall	4,960,121 A	10/1990	Nelson et al.
4,579,113 A	4/1986	McCreadie et al.	4,966,590 A	10/1990	Kalt
4,587,967 A	5/1986	Chu et al.	4,969,880 A	11/1990	Zamierowski
4,593,688 A	6/1986	Payton	4,971,051 A	11/1990	Toffolon
4,601,465 A	7/1986	Roy	D313,277 S	12/1990	Haining
D285,496 S	9/1986	Berman	4,976,698 A	12/1990	Stokley
4,616,647 A	10/1986	McCreadie	4,986,269 A	1/1991	Hakkinen
4,617,637 A	10/1986	Chu et al.	4,989,271 A	2/1991	Sapiejewski et al.
4,622,964 A	11/1986	Flynn	4,989,596 A	2/1991	Macris et al.
4,630,604 A	12/1986	Montesi	4,989,599 A	2/1991	Carter
4,641,645 A	2/1987	Tayebi	4,996,983 A	3/1991	AmRhein
4,641,647 A	2/1987	Behan	5,000,173 A	3/1991	Zalkin et al.
D289,238 S	4/1987	Arthur, Jr.	5,003,631 A	4/1991	Richardson
4,655,213 A	4/1987	Rapoport et al.	5,003,633 A	4/1991	Itoh
4,657,010 A	4/1987	Wright	5,005,568 A	4/1991	Loescher et al.
4,660,555 A	4/1987	Payton	5,005,571 A	4/1991	Dietz
4,665,570 A	5/1987	Davis	5,018,519 A	5/1991	Brown
4,671,267 A	6/1987	Stout	5,020,163 A	6/1991	Aileo et al.
4,671,271 A	6/1987	Bishop et al.	5,022,900 A	6/1991	Bar-Yona et al.
4,674,134 A	6/1987	Lundin	5,023,955 A	6/1991	Murphy, II et al.
4,676,241 A	6/1987	Webb et al.	5,025,805 A	6/1991	Nutter
4,677,975 A	7/1987	Edgar et al.	5,027,809 A	7/1991	Robinson
4,677,977 A	7/1987	Wilcox	5,038,772 A	8/1991	Kolbe et al.
4,686,977 A	8/1987	Cosma	5,038,776 A	8/1991	Harrison et al.
4,699,139 A	10/1987	Marshall et al.	5,042,473 A	8/1991	Lewis
4,706,664 A	11/1987	Snook et al.	5,042,478 A	8/1991	Kopala et al.
4,707,863 A	11/1987	McNeal	5,046,200 A	9/1991	Feder
4,711,636 A	12/1987	Bierman	5,046,491 A	9/1991	Derrick
4,713,844 A	12/1987	Westgate	5,062,421 A	11/1991	Burns et al.
H397 H	1/1988	Stark	5,063,922 A	11/1991	Hakkinen
D293,613 S	1/1988	Wingler	5,069,205 A	12/1991	Urso
4,739,755 A	4/1988	White et al.	5,074,297 A	12/1991	Venegas
4,753,233 A	6/1988	Grimes	5,080,092 A	1/1992	Tenna
4,767,411 A	8/1988	Edmunds	D323,908 S	2/1992	Hollister et al.
4,770,169 A	9/1988	Schmoegner et al.	5,093,940 A	3/1992	Nishiyama
4,772,760 A	9/1988	Graham	5,109,839 A	5/1992	Blasdel et al.
4,774,941 A	10/1988	Cook	5,109,840 A	5/1992	Daleiden
4,774,946 A	10/1988	Ackerman et al.	5,113,857 A	5/1992	Dickerman et al.
4,782,832 A	11/1988	Trimble et al.	5,117,818 A	6/1992	Palfy
4,790,829 A	12/1988	Bowden et al.	5,121,745 A	6/1992	Israel
4,799,477 A	1/1989	Lewis	5,121,746 A	6/1992	Sikora
4,802,857 A	2/1989	Laughlin	5,123,677 A	6/1992	Kreczko et al.
4,803,981 A	2/1989	Vickery	5,127,397 A	7/1992	Kohnke
4,807,617 A	2/1989	Nesti	5,133,347 A	7/1992	Huennebeck
4,809,692 A	3/1989	Nowacki et al.	5,137,017 A	8/1992	Salter
4,811,730 A	3/1989	Milano	5,138,722 A	8/1992	Urella et al.
4,819,629 A	4/1989	Jonson	5,140,980 A	8/1992	Haughey et al.
4,821,713 A	4/1989	Bauman	5,140,982 A	8/1992	Bauman
4,827,924 A	5/1989	Japuntich	5,146,914 A	9/1992	Sturrock
4,830,138 A	5/1989	Palmaer et al.	5,159,938 A	11/1992	Laughlin
			5,178,138 A	1/1993	Walstrom et al.
			5,181,506 A	1/1993	Tardiff, Jr. et al.
			D333,015 S	2/1993	Farmer et al.
			5,188,101 A	2/1993	Tumolo

(56)

References Cited

U.S. PATENT DOCUMENTS

D334,633 S	4/1993	Rudolph	5,509,404 A	4/1996	Lloyd et al.
5,199,424 A	4/1993	Sullivan et al.	5,509,409 A	4/1996	Weatherholt
D335,322 S	5/1993	Jones	5,511,541 A	4/1996	Dearstine
5,207,665 A	5/1993	Davis et al.	5,513,634 A	5/1996	Jackson
5,220,699 A	6/1993	Farris	5,513,635 A	5/1996	Bedi
5,222,478 A	6/1993	Scarberry et al.	5,517,986 A	5/1996	Starr et al.
5,231,983 A	8/1993	Matson et al.	5,522,382 A	6/1996	Sullivan et al.
5,233,978 A	8/1993	Callaway	5,526,806 A	6/1996	Sansoni
5,243,709 A	9/1993	Sheehan et al.	5,533,506 A	7/1996	Wood
5,243,971 A	9/1993	Sullivan et al.	5,538,000 A	7/1996	Rudolph
5,245,995 A	9/1993	Sullivan et al.	5,538,001 A	7/1996	Bridges
5,263,939 A	11/1993	Wortrich	5,540,223 A	7/1996	Starr et al.
5,265,592 A	11/1993	Beaussant	5,542,128 A	8/1996	Lomas
5,265,595 A	11/1993	Rudolph	5,546,936 A	8/1996	Virag et al.
5,267,557 A	12/1993	Her-Mou	5,558,090 A	9/1996	James
5,269,296 A	12/1993	Landis	RE35,339 E	10/1996	Rapoport
5,271,391 A	12/1993	Graves	5,560,354 A	10/1996	Berthon-Jones et al.
5,279,289 A	1/1994	Kirk	5,568,946 A	10/1996	Jackowski
5,280,784 A	1/1994	Kohler	5,570,682 A	11/1996	Johnson
5,291,880 A	3/1994	Almovist et al.	5,570,684 A	11/1996	Behr
5,299,448 A	4/1994	Maryanek et al.	5,570,689 A	11/1996	Starr et al.
5,299,579 A	4/1994	Gedeon et al.	5,575,278 A	11/1996	Bonhomme et al.
5,299,599 A	4/1994	Farmer et al.	D377,089 S	12/1996	Starr et al.
5,301,689 A	4/1994	Wennerholm	5,592,937 A	1/1997	Freund
5,304,146 A	4/1994	Johnson et al.	5,592,938 A	1/1997	Scarberry et al.
5,311,862 A	5/1994	Blasdel et al.	5,608,647 A	3/1997	Rubsamen et al.
5,322,057 A	6/1994	Raabe et al.	5,617,849 A	4/1997	Springett et al.
5,322,059 A	6/1994	Walther	5,623,923 A	4/1997	Bertheau et al.
5,331,691 A	7/1994	Runckel	5,642,726 A	7/1997	Owens et al.
D349,586 S	8/1994	Handke	5,642,730 A	7/1997	Baran
5,334,646 A	8/1994	Chen	5,645,054 A	7/1997	Cotner et al.
5,335,656 A	8/1994	Bowe et al.	5,647,355 A	7/1997	Starr et al.
5,343,878 A	9/1994	Scarberry et al.	5,647,356 A	7/1997	Osendorf et al.
5,349,949 A	9/1994	Schegerin	5,647,357 A	7/1997	Barnett et al.
5,353,789 A	10/1994	Schlobohm	5,649,532 A	7/1997	Griffiths
5,355,878 A	10/1994	Griffiths et al.	5,649,533 A	7/1997	Oren
5,355,893 A	10/1994	Mick et al.	5,653,228 A	8/1997	Byrd
5,357,945 A	10/1994	Messina	5,655,520 A	8/1997	Howe et al.
5,357,951 A	10/1994	Ratner	5,655,527 A	8/1997	Scarberry et al.
5,364,367 A	11/1994	Banks et al.	5,657,493 A	8/1997	Ferrero et al.
5,372,130 A	12/1994	Stern et al.	5,657,752 A	8/1997	Landis et al.
5,372,388 A	12/1994	Gargiulo	5,660,171 A	8/1997	Kimm et al.
5,372,389 A	12/1994	Tam et al.	5,660,174 A	8/1997	Jacobelli
5,372,390 A	12/1994	Conway et al.	5,662,101 A	9/1997	Ogden et al.
5,372,391 A	12/1994	Bast et al.	5,666,946 A	9/1997	Langenback
5,375,593 A	12/1994	Press	5,676,133 A	10/1997	Hickle et al.
5,385,141 A	1/1995	Granatiero	D385,960 S	11/1997	Rudolph
5,388,571 A	2/1995	Roberts et al.	5,682,881 A	11/1997	Winthrop et al.
5,390,373 A	2/1995	Flory	5,685,296 A	11/1997	Zdrojowski et al.
5,391,248 A	2/1995	Brain	5,687,715 A	11/1997	Landis et al.
5,394,568 A	3/1995	Brostrom et al.	D389,238 S	1/1998	Kirk, III et al.
5,396,885 A	3/1995	Nelson	5,704,345 A	1/1998	Berthon-Jones
5,398,676 A	3/1995	Press et al.	5,707,342 A	1/1998	Tanaka
5,400,776 A	3/1995	Bartholomew	5,709,204 A	1/1998	Lester
5,400,781 A	3/1995	Davenport	5,715,814 A	2/1998	Ebers
5,404,871 A	4/1995	Goodman et al.	5,724,964 A	3/1998	Brunson et al.
5,419,317 A	5/1995	Blasdel et al.	5,724,965 A	3/1998	Handke et al.
5,419,318 A	5/1995	Tayebi	5,735,272 A	4/1998	Dillon et al.
5,425,359 A	6/1995	Liou	5,740,799 A	4/1998	Nielsen
5,429,126 A	7/1995	Bracken	5,746,201 A	5/1998	Kidd
5,429,683 A	7/1995	Le Mitouard	5,752,509 A	5/1998	Lachmann et al.
5,431,158 A	7/1995	Tirotta	5,752,511 A	5/1998	Simmons et al.
5,437,267 A	8/1995	Weinstein et al.	5,778,872 A	7/1998	Fukunaga et al.
5,438,981 A	8/1995	Starr et al.	5,782,774 A	7/1998	Shmulewitz
5,441,046 A	8/1995	Starr et al.	5,794,615 A	8/1998	Estes
D362,061 S	9/1995	McGinnis et al.	5,794,617 A	8/1998	Brunell et al.
5,462,528 A	10/1995	Roewer	5,794,619 A	8/1998	Edelman et al.
5,477,852 A	12/1995	Landis et al.	D398,987 S	9/1998	Cotner et al.
5,479,920 A	1/1996	Piper et al.	5,807,341 A	9/1998	Heim
5,481,763 A	1/1996	Brostrom et al.	5,813,423 A	9/1998	Kirchgeorg
5,485,837 A	1/1996	Solesbee et al.	5,832,918 A	11/1998	Pantino
5,488,948 A	2/1996	Dubruille et al.	D402,755 S	12/1998	Kwok
5,492,116 A	2/1996	Scarberry et al.	5,842,469 A	12/1998	Rapp et al.
5,501,214 A	3/1996	Sabo	RE36,165 E	3/1999	Behr
5,503,147 A	4/1996	Bertheau	5,884,624 A	3/1999	Barnett et al.
			5,887,587 A	3/1999	Groenke
			5,896,857 A	4/1999	Hely et al.
			5,906,203 A	5/1999	Klockseth et al.
			5,909,732 A	6/1999	Diesel et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,918,598 A	7/1999	Belfer et al.	6,434,796 B1	8/2002	Speirs
5,921,239 A	7/1999	McCall et al.	6,435,181 B1	8/2002	Jones, Jr. et al.
D412,745 S	8/1999	Scheu	6,439,230 B1	8/2002	Gunaratnam et al.
5,935,136 A	8/1999	Hulse et al.	6,439,234 B1	8/2002	Curti et al.
5,937,445 A	8/1999	Ravo et al.	6,448,303 B1	9/2002	Paul
5,937,851 A	8/1999	Serowski et al.	6,457,473 B1	10/2002	Brostrom et al.
5,954,049 A	9/1999	Foley et al.	6,463,931 B1	10/2002	Kwok et al.
5,964,485 A	10/1999	Hame et al.	6,467,482 B1	10/2002	Boussignac
5,966,745 A	10/1999	Schwartz et al.	6,467,483 B1	10/2002	Kopacko et al.
5,970,975 A	10/1999	Estes et al.	6,470,887 B1	10/2002	Martinez
5,975,079 A	11/1999	Hellings et al.	6,478,026 B1	11/2002	Wood
6,003,511 A	12/1999	Fukunaga et al.	6,482,178 B1	11/2002	Andrews et al.
6,006,748 A	12/1999	Hollis	6,491,034 B1	12/2002	Gunaratnam et al.
D419,658 S	1/2000	Matchett et al.	D468,823 S	1/2003	Smart
6,016,804 A	1/2000	Gleason et al.	6,513,526 B2	2/2003	Kwok et al.
D421,298 S	2/2000	Kenyon et al.	6,520,182 B1	2/2003	Gunaratnam
6,019,101 A	2/2000	Cotner et al.	6,530,373 B1	3/2003	Patron et al.
6,026,811 A	2/2000	Settle	6,532,961 B1	3/2003	Kwok et al.
6,029,660 A	2/2000	Calluau et al.	6,536,435 B1	3/2003	Fecteau et al.
6,029,665 A	2/2000	Berthon-Jones	6,557,556 B2	5/2003	Kwok et al.
6,039,044 A	3/2000	Sullivan	6,561,188 B1	5/2003	Ellis
D423,096 S	4/2000	Kwok	6,561,190 B1	5/2003	Kwok
6,044,844 A	4/2000	Kwok et al.	6,561,191 B1	5/2003	Kwok
6,082,360 A	7/2000	Rudolph et al.	6,561,192 B2	5/2003	Palmer
6,086,118 A	7/2000	Mc Naughton et al.	6,561,193 B1	5/2003	Noble
6,091,973 A	7/2000	Colla et al.	6,571,798 B1	6/2003	Thornton
D428,987 S	8/2000	Kwok	6,579,267 B2	6/2003	Lynch et al.
6,095,996 A	8/2000	Steer et al.	6,581,601 B2	6/2003	Ziaee
6,102,040 A	8/2000	Tayebi et al.	6,581,602 B2	6/2003	Kwok et al.
6,109,263 A	8/2000	Feuchtgruber	6,584,975 B1	7/2003	Taylor
6,112,746 A	9/2000	Kwok et al.	6,595,214 B1	7/2003	Hecker et al.
6,119,693 A	9/2000	Kwok et al.	6,595,215 B2	7/2003	Wood
6,119,694 A	9/2000	Correa et al.	6,607,516 B2	8/2003	Cinelli et al.
6,123,071 A	9/2000	Berthon-Jones et al.	6,615,830 B1	9/2003	Serowski et al.
6,123,082 A	9/2000	Berthon-Jones	6,615,832 B1	9/2003	Chen
6,139,787 A	10/2000	Harrison	6,626,177 B1	9/2003	Ziaee
6,152,137 A	11/2000	Schwartz et al.	6,627,289 B1	9/2003	Dilnik et al.
6,155,253 A	12/2000	Gamberini	6,631,718 B1	10/2003	Lovell
6,192,886 B1	2/2001	Rudolph	6,634,358 B2	10/2003	Kwok et al.
6,193,914 B1	2/2001	Harrison	6,637,434 B2	10/2003	Noble
D439,326 S	3/2001	Hecker et al.	6,644,315 B2	11/2003	Ziaee
6,196,223 B1	3/2001	Belfer et al.	6,651,663 B2	11/2003	Barnett et al.
6,211,263 B1	4/2001	Cinelli et al.	D484,237 S	12/2003	Lang et al.
6,213,125 B1	4/2001	Reese et al.	6,655,385 B1	12/2003	Curti et al.
6,231,548 B1	5/2001	Bassett	6,663,600 B2	12/2003	Bierman et al.
D443,355 S	6/2001	Gunaratnam et al.	6,669,712 B1	12/2003	Cardoso
6,241,930 B1	6/2001	Harrison	D485,905 S	1/2004	Moore et al.
6,257,237 B1	7/2001	Suzuki	6,679,257 B1	1/2004	Robertson et al.
6,257,626 B1	7/2001	Campau	6,679,261 B2	1/2004	Lithgow
6,258,066 B1	7/2001	Urich	6,679,265 B2	1/2004	Strickland et al.
6,279,573 B1	8/2001	Johnson et al.	6,691,707 B1	2/2004	Gunaratnam et al.
6,295,366 B1	9/2001	Haller et al.	6,691,708 B2	2/2004	Kwok et al.
6,328,031 B1	12/2001	Tischer et al.	6,701,535 B2	3/2004	Dobbie et al.
6,328,038 B1	12/2001	Kessler et al.	6,701,926 B2	3/2004	Olsen et al.
6,340,024 B1	1/2002	Brookman et al.	6,701,927 B2	3/2004	Kwok et al.
6,341,606 B1	1/2002	Bordewick et al.	6,710,099 B2	3/2004	Cinelli et al.
6,345,618 B1	2/2002	Hayek	6,712,072 B1	3/2004	Lang
6,347,631 B1	2/2002	Hansen et al.	6,729,333 B2	5/2004	Barnett et al.
6,357,440 B1	3/2002	Hansen et al.	D492,992 S	7/2004	Guney et al.
6,357,441 B1	3/2002	Kwok et al.	D493,521 S	7/2004	Guney
6,358,279 B1	3/2002	Tahi et al.	6,766,800 B2	7/2004	Chu et al.
6,371,110 B1	4/2002	Peterson et al.	6,766,817 B2	7/2004	da Silva
6,374,826 B1	4/2002	Gunaratnam et al.	6,772,760 B2	8/2004	Frater et al.
6,388,640 B1	5/2002	Chigira et al.	6,776,162 B2	8/2004	Wood
6,397,847 B1	6/2002	Scarberry et al.	6,776,163 B2	8/2004	Dougill et al.
6,412,487 B1	7/2002	Gunaratnam et al.	6,789,543 B2	9/2004	Cannon
6,412,488 B1	7/2002	Barnett et al.	6,796,308 B2	9/2004	Gunaratnam et al.
6,412,593 B1	7/2002	Jones	6,805,117 B1	10/2004	Ho et al.
6,418,928 B1	7/2002	Bordewick et al.	6,807,967 B2	10/2004	Wood
6,419,660 B1	7/2002	Russo	6,817,362 B2	11/2004	Gelinas et al.
6,422,238 B1	7/2002	Lithgow	6,820,617 B2	11/2004	Robertson et al.
6,423,036 B1	7/2002	Van Huizen	6,823,865 B2	11/2004	Drew et al.
6,425,395 B1	7/2002	Brewer et al.	6,823,869 B2	11/2004	Raje et al.
6,427,694 B1	8/2002	Hecker et al.	6,834,650 B1	12/2004	Fini
6,431,172 B1	8/2002	Bordewick	6,851,425 B2	2/2005	Jaffre
			6,851,428 B2	2/2005	Dennis
			6,851,429 B2	2/2005	Bishop
			6,860,269 B2	3/2005	Kwok et al.
			6,860,270 B2	3/2005	Sniadach

(56)

References Cited

U.S. PATENT DOCUMENTS

6,871,649 B2	3/2005	Kwok et al.	7,775,209 B2	8/2010	Biener et al.
6,892,729 B2	5/2005	Smith et al.	7,779,832 B1	8/2010	Ho
6,895,965 B2	5/2005	Scarberry et al.	7,798,144 B2	9/2010	Kwok et al.
6,907,882 B2	6/2005	Ging	7,814,911 B2	10/2010	Bordewick et al.
6,914,091 B2	7/2005	Donald et al.	7,819,119 B2	10/2010	Ho
6,918,404 B2	7/2005	Dias da Silva	7,827,990 B1	11/2010	Melidis et al.
6,926,004 B2	8/2005	Schumacher	7,841,345 B2	11/2010	Guney et al.
6,938,620 B2	9/2005	Payne, Jr.	7,856,980 B2	12/2010	Lang et al.
6,959,710 B2	11/2005	Barnett et al.	7,856,982 B2	12/2010	Matula, Jr. et al.
6,968,844 B2	11/2005	Liland	7,861,715 B2	1/2011	Jones et al.
6,972,003 B2	12/2005	Bierman et al.	7,874,293 B2	1/2011	Gunaratnam et al.
6,986,352 B2	1/2006	Frater et al.	7,878,199 B2	2/2011	Ging et al.
6,997,177 B2	2/2006	Wood	7,900,631 B2	3/2011	Persson
7,000,614 B2	2/2006	Lang et al.	7,900,635 B2	3/2011	Gunaratnam et al.
7,007,696 B2	3/2006	Palkon et al.	7,931,024 B2	4/2011	Ho et al.
7,011,090 B2	3/2006	Drew et al.	7,958,893 B2	6/2011	Lithgow et al.
7,018,362 B2	3/2006	Bierman et al.	7,967,013 B2	6/2011	Ging et al.
7,040,321 B2	5/2006	Gobel	7,967,014 B2	6/2011	Heidmann et al.
7,052,127 B2	5/2006	Harrison	7,971,590 B2	7/2011	Frater et al.
7,059,326 B2	6/2006	Heidmann et al.	7,992,559 B2	8/2011	Lang et al.
7,066,586 B2	6/2006	da Silva	7,997,267 B2	8/2011	Ging et al.
7,069,932 B2	7/2006	Eaton et al.	8,042,538 B2	10/2011	Ging et al.
7,076,282 B2	7/2006	Munro et al.	8,042,541 B2	10/2011	Amarasinghe et al.
7,076,822 B2	7/2006	Pearce	8,042,542 B2	10/2011	Ging et al.
7,080,645 B2	7/2006	Genger et al.	8,042,546 B2	10/2011	Gunaratnam et al.
7,093,599 B2	8/2006	Chen	8,051,850 B2	11/2011	Kwok et al.
7,100,610 B2	9/2006	Biener et al.	8,091,553 B2	1/2012	Bordewick et al.
7,101,359 B2	9/2006	Kline et al.	8,096,301 B2	1/2012	Smith et al.
7,107,989 B2	9/2006	Frater et al.	8,136,524 B2	3/2012	Ging et al.
7,114,497 B2	10/2006	Aylsworth et al.	8,136,525 B2	3/2012	Lubke et al.
7,121,279 B2	10/2006	Dennis	8,186,352 B2	5/2012	Gunaratnam et al.
7,146,976 B2	12/2006	McKown	8,210,180 B2	7/2012	Gunaratnam
7,152,599 B2	12/2006	Thomas	8,220,459 B2	7/2012	Davidson et al.
7,152,601 B2	12/2006	Barakat et al.	8,297,283 B2	10/2012	Hitchcock et al.
7,178,525 B2	2/2007	Matula, Jr. et al.	8,397,728 B2	3/2013	D'Souza et al.
7,185,652 B2	3/2007	Gunaratnam et al.	2001/0020474 A1	9/2001	Hecker et al.
7,191,781 B2	3/2007	Wood	2002/0020416 A1	2/2002	Namey
7,207,328 B1	4/2007	Altemus	2002/0029780 A1	3/2002	Frater et al.
7,207,335 B2	4/2007	Kwok et al.	2002/0046755 A1	4/2002	DeVoss
7,210,481 B1	5/2007	Lovell et al.	2002/0066452 A1	6/2002	Kessler et al.
7,216,647 B2	5/2007	Lang et al.	2002/0069872 A1	6/2002	Gradon et al.
7,237,551 B2	7/2007	Ho et al.	2002/0124849 A1	9/2002	Billette De Villemeur
7,243,723 B2	7/2007	Surjaatmadja	2002/0143296 A1	10/2002	Russo
D550,836 S	9/2007	Chandran et al.	2002/0157673 A1	10/2002	Kessler et al.
D552,733 S	10/2007	Crisuolo et al.	2002/0174868 A1	11/2002	Kwok et al.
7,285,255 B2	10/2007	Kadlec et al.	2003/0019495 A1	1/2003	Palkon et al.
7,302,950 B2	12/2007	Berthon-Jones et al.	2003/0062048 A1	4/2003	Gradon et al.
7,308,895 B2	12/2007	Wixey et al.	2003/0089373 A1	5/2003	Gradon et al.
7,318,437 B2	1/2008	Gunaratnam	2003/0168063 A1	9/2003	Gambone et al.
7,318,439 B2	1/2008	Raje et al.	2003/0196656 A1	10/2003	Moore et al.
7,320,323 B2	1/2008	Lang et al.	2003/0196658 A1	10/2003	Ging et al.
7,341,060 B2	3/2008	Ging et al.	2004/0025883 A1	2/2004	Eaton et al.
7,353,826 B2	4/2008	Sleeper et al.	2004/0094157 A1	5/2004	Dantanarayana et al.
7,461,656 B2	12/2008	Gunaratnam et al.	2004/0106891 A1	6/2004	Langan et al.
7,470,256 B2	12/2008	Lampropoulos et al.	2004/0111104 A1	6/2004	Schein et al.
7,481,220 B2	1/2009	Meyer et al.	2004/0112384 A1	6/2004	Lithgow et al.
7,487,772 B2	2/2009	Ging et al.	2004/0112385 A1	6/2004	Drew et al.
7,503,327 B2	3/2009	Gunaratnam	2004/0127856 A1	7/2004	Johnson
7,509,958 B2	3/2009	Amarasinghe et al.	2004/0177850 A1	9/2004	Gradon et al.
7,520,869 B2	4/2009	Lampropoulos et al.	2004/0182398 A1	9/2004	Sprinkle et al.
7,523,754 B2	4/2009	Lithgow	2004/0211428 A1	10/2004	Jones
7,562,658 B2	7/2009	Madaus et al.	2004/0226566 A1	11/2004	Gunaratnam et al.
7,614,400 B2	11/2009	Lithgow et al.	2005/0011521 A1	1/2005	Sprinkle et al.
7,614,401 B2	11/2009	Thompson	2005/0022820 A1 *	2/2005	Kwok et al. 128/206.21
7,621,274 B2	11/2009	Sprinkle et al.	2005/0051171 A1	3/2005	Booth
7,624,735 B2	12/2009	Ho et al.	2005/0051176 A1	3/2005	Riggins
7,640,934 B2	1/2010	Zollinger et al.	2005/0056286 A1	3/2005	Huddart et al.
7,654,263 B2	2/2010	Lang et al.	2005/0061326 A1	3/2005	Payne, Jr.
7,658,189 B2	2/2010	Davidson et al.	2005/0098183 A1	5/2005	Nash et al.
7,665,464 B2	2/2010	Kopacko et al.	2005/0150495 A1	7/2005	Rittner et al.
7,699,808 B2	4/2010	Marrs et al.	2005/0155604 A1	7/2005	Ging et al.
7,703,457 B2	4/2010	Barnett et al.	2005/0211252 A1	9/2005	Lang et al.
7,708,017 B2	5/2010	Davidson	2005/0241644 A1	11/2005	Gunaratnam et al.
7,743,767 B2	6/2010	Ging et al.	2006/0042629 A1 *	3/2006	Geist 128/206.24
7,762,259 B2	7/2010	Gunaratnam	2006/0076017 A1	4/2006	Walker et al.
			2006/0107960 A1 *	5/2006	Smart 128/206.24
			2006/0118117 A1	6/2006	Berthon-Jones et al.
			2006/0124131 A1	6/2006	Chandran et al.
			2006/0137690 A1	6/2006	Gunaratnam et al.

(56)

References Cited

FOREIGN PATENT DOCUMENTS

U.S. PATENT DOCUMENTS				AU	95/16178	7/1995
				AU	94/59430	10/1995
2006/0174887	A1	8/2006	Chandran et al.	AU	95/32914	2/1996
2006/0207597	A1	9/2006	Wright	AU	96/51130	10/1996
2006/0213520	A1	9/2006	Frater et al.	AU	97/41018	4/1998
2006/0272646	A1	12/2006	Ho et al.	AU	98/89312	1/1999
2006/0283461	A1	12/2006	Lubke et al.	AU	2005100738	11/2005
2007/0044804	A1	3/2007	Matula, Jr. et al.	AU	2006/00031	1/2006
2007/0137653	A1	6/2007	Wood	CA	618807	4/1961
2007/0144525	A1	6/2007	Davidson et al.	CA	623129	7/1961
2007/0163600	A1	7/2007	Hoffman	CA	1039144	9/1978
2007/0215161	A1	9/2007	Frater et al.	CN	1219883	6/1999
2007/0221226	A1	9/2007	Hansen et al.	CN	2464353	12/2001
2007/0267017	A1	11/2007	McAuley et al.	CN	1735439	2/2006
2007/0272249	A1	11/2007	Chandran et al.	CN	2902337	Y 5/2007
2007/0282272	A1	12/2007	Bannon et al.	DE	185 017	5/1907
2008/0004573	A1	1/2008	Kaufmann et al.	DE	284 800	11/1913
2008/0006277	A1	1/2008	Worboys et al.	DE	459 104	4/1928
2008/0047560	A1	2/2008	Veliss et al.	DE	701 690	1/1941
2008/0060649	A1	3/2008	Veliss et al.	DE	30 11 900	10/1980
2008/0065022	A1	3/2008	Kyvik et al.	DE	146 688	1/1981
2008/0110464	A1	5/2008	Davidson et al.	DE	30 15 279	10/1981
2008/0110469	A1	5/2008	Weinberg	DE	31 49 449	10/1982
2008/0178875	A1	7/2008	Henry	DE	159 396	3/1983
2008/0178886	A1	7/2008	Lieberman et al.	DE	33 45 067	6/1984
2008/0200880	A1	8/2008	Kyvik et al.	DE	37 07 952	3/1987
2008/0257354	A1	10/2008	Davidson et al.	DE	35 37 507	4/1987
2008/0302365	A1	12/2008	Cohen et al.	DE	35 39 073	5/1987
2008/0314389	A1	12/2008	Thomas et al.	DE	37 19 009	12/1988
2009/0044808	A1	2/2009	Guney et al.	DE	39 27 038	2/1991
2009/0126739	A1	5/2009	Ng et al.	DE	40 04 157	4/1991
2009/0139526	A1	6/2009	Melidis et al.	DE	42 12 259	1/1993
2009/0139527	A1	6/2009	Ng et al.	DE	42 33 448	4/1993
2009/0151729	A1	6/2009	Judson et al.	DE	43 43 205	6/1995
2009/0173343	A1	7/2009	Omura et al.	DE	195 48 380	7/1996
2009/0217929	A1	9/2009	Kwok et al.	DE	196 03 949	8/1997
2009/0223518	A1	9/2009	Kwok et al.	DE	297 15 718	10/1997
2009/0223521	A1	9/2009	Howard et al.	DE	197 35 359	1/1998
2010/0000534	A1	1/2010	Kooij et al.	DE	297 23 101	7/1998
2010/0000543	A1	1/2010	Berthon-Jones et al.	DE	197 03 526	8/1998
2010/0018534	A1	1/2010	Veliss et al.	DE	298 10 846	8/1998
2010/0089401	A1	4/2010	Lang et al.	DE	198 17 332	1/1999
2010/0132717	A1	6/2010	Davidson et al.	DE	198 07 961	8/1999
2010/0192955	A1	8/2010	Biener et al.	DE	198 08 105	9/1999
2010/0282265	A1	11/2010	Melidis et al.	DE	198 40 760	3/2000
2010/0300447	A1	12/2010	Biener et al.	DE	200 05 346	5/2000
2010/0319700	A1	12/2010	Ng et al.	DE	299 23 141	5/2000
2011/0030692	A1	2/2011	Jones et al.	DE	200 17 940	2/2001
2011/0056497	A1	3/2011	Scheiner et al.	DE	199 44 242	3/2001
2011/0220110	A1	9/2011	Frater et al.	DE	199 54 517	6/2001
2011/0220114	A1	9/2011	Lithgow et al.	DE	100 02 571	7/2001
2011/0226254	A1	9/2011	Lang et al.	DE	199 62 515	7/2001
2011/0259337	A1	10/2011	Hitchcock et al.	DE	100 45 183	5/2002
2012/0138063	A1	6/2012	Eves et al.	DE	102 13 905	10/2002
2012/0174928	A1	7/2012	Raje et al.	DE	10 2004 055 4	11/2004
2012/0266886	A1	10/2012	Davidson et al.	DE	103 31 837	1/2005
2013/0037033	A1	2/2013	Hitchcock et al.	DE	20 2004 018 108	2/2005
2013/0081628	A1	4/2013	Davidson et al.	DE	103 38 169	3/2005
2013/0081629	A1	4/2013	Davidson et al.	EP	0 054 154	6/1982
2013/0081630	A1	4/2013	Davidson et al.	EP	0 252 052	1/1988
2013/0081631	A1	4/2013	Davidson et al.	EP	0 264 772	4/1988
2013/0081632	A1	4/2013	Davidson et al.	EP	0 288 937	11/1988
2013/0086795	A1	4/2013	Davidson et al.	EP	0 334 555	9/1989
2013/0086796	A1	4/2013	Davidson et al.	EP	0 386 605	9/1990
2013/0087147	A1	4/2013	Davidson et al.	EP	0 427 474	5/1991
2013/0087148	A1	4/2013	Davidson et al.	EP	0 462 701	12/1991
2013/0087149	A1	4/2013	Davidson et al.	EP	0 466 960	1/1992
2013/0092168	A1	4/2013	Davidson et al.	EP	0 303 090	B1 4/1992
2013/0092170	A1	4/2013	Davidson et al.	EP	0 549 299	6/1993
2013/0133658	A1	5/2013	Ng et al.	EP	0 602 424	6/1994
2013/0133660	A1	5/2013	Ng et al.	EP	0 608 684	8/1994
2013/0327333	A1	12/2013	Ng et al.	EP	0 658 356	6/1995
				EP	0 697 225	2/1996
				EP	0 178 925	A2 4/1996
				EP	0 747 078	12/1996
				EP	0 776 679	6/1997
				EP	0 821 978	2/1998

(56) References Cited					
FOREIGN PATENT DOCUMENTS			WO	WO 97/41911	11/1997
EP	0 853 962	7/1998	WO	WO 98/03145	1/1998
EP	1 027 905	8/2000	WO	WO 98/04310	2/1998
EP	1 057 494	12/2000	WO	WO 98/11930	3/1998
EP	1 099 452	5/2001	WO	WO 98/12965	4/1998
EP	1 118 346	7/2001	WO	WO 98/18514	5/1998
EP	1 163 923	12/2001	WO	WO 98/23305	6/1998
EP	0 830 180 B1	3/2002	WO	WO 98/24499	6/1998
EP	1 205 205	5/2002	WO	WO 98/26829	6/1998
EP	1 258 266	11/2002	WO	WO 98/26830	6/1998
EP	1 356 843	10/2003	WO	WO 98/34665	8/1998
EP	1 360 971	11/2003	WO	WO 98/48878	11/1998
EP	1 481 702	12/2004	WO	WO 99/16327	4/1999
EP	2 471 566	7/2012	WO	WO 99/25410	5/1999
EP	2 471 567	7/2012	WO	WO 99/43375	9/1999
FR	780018	4/1935	WO	WO 99/58181	11/1999
FR	2 574 657	6/1986	WO	WO 99/61088	12/1999
FR	2 658 725	8/1991	WO	WO 99/65554	12/1999
FR	2 720 280	12/1995	WO	WO 00/20072	4/2000
FR	2 749 176	12/1997	WO	WO 00/21600	4/2000
FR	2 823 122	10/2002	WO	WO 00/35525	6/2000
GB	532 214	1/1941	WO	WO 00/38772	7/2000
GB	649 689	1/1951	WO	WO 00/50121	8/2000
GB	823 887	11/1959	WO	WO 00/57942	10/2000
GB	880942	10/1961	WO	WO 00/69521	11/2000
GB	1 395 391	5/1975	WO	WO 00/72905	12/2000
GB	1 467 828	3/1977	WO	WO 00/74758	12/2000
GB	2 145 335	3/1985	WO	WO 00/76568	12/2000
GB	2 147 506	5/1985	WO	WO 00/78381	12/2000
GB	2 164 569	3/1986	WO	WO 00/78384	12/2000
GB	2 176 404	12/1986	WO	WO 01/62326	8/2001
GB	2 186 801	8/1987	WO	WO 01/95965	12/2001
GB	2 267 648	12/1993	WO	WO 01/97892	12/2001
GB	2 368 533	5/2002	WO	WO 01/97893	12/2001
GB	2 385 533	5/2003	WO	WO 02/11804	2/2002
JP	S39-13991	7/1964	WO	WO 02/32491	4/2002
JP	S51-142793	11/1976	WO	WO 02/38221	5/2002
JP	H03-007173	1/1991	WO	WO 02/45784	6/2002
JP	H09-216240	8/1997	WO	WO 03/005931	1/2003
JP	H11-000397	1/1999	WO	WO 03/059427	7/2003
JP	H11-104256	4/1999	WO	WO 03/082406	10/2003
JP	H11-508159	7/1999	WO	WO 03/090827	11/2003
JP	2000-279520	10/2000	WO	WO 03/105921	12/2003
JP	2000-325481	11/2000	WO	WO 2004/007010	1/2004
JP	2000-515784	11/2000	WO	WO 2004/022144	3/2004
JP	2002-028240	4/2002	WO	WO 2004/022145	3/2004
JP	2002-543943	12/2002	WO	WO 2004/022146	3/2004
JP	2003-175106	6/2003	WO	WO 2004/022147	3/2004
JP	2003-535657	12/2003	WO	WO 2004/041342	5/2004
JP	2004-000570	1/2004	WO	WO 2004/071565 A1	8/2004
JP	2005-337371	12/2005	WO	WO 2004/073778	9/2004
JP	3802872	7/2006	WO	WO 2004/078228	9/2004
JP	2008/501438	1/2008	WO	WO 2004/078230	9/2004
WO	WO 80/01044	5/1980	WO	WO 2004/096332	11/2004
WO	WO 82/03548	10/1982	WO	WO 2005/002656	1/2005
WO	WO 86/06969	12/1986	WO	WO 2005/018523	3/2005
WO	WO 87/01950	4/1987	WO	WO 2005/021075	3/2005
WO	WO 91/03277	3/1991	WO	WO 2005/028010	3/2005
WO	WO 92/15353	9/1992	WO	WO 2005/053781	6/2005
WO	WO 92/20392	11/1992	WO	WO 2005/063326	7/2005
WO	WO 92/20395	11/1992	WO	WO 2005/063328	7/2005
WO	WO 93/01854	2/1993	WO	WO 2005/086943	9/2005
WO	WO 93/24169	12/1993	WO	WO 2005/094928	10/2005
WO	WO 94/02190	2/1994	WO	WO 2005/099801	10/2005
WO	WO 94/16759	8/1994	WO	WO 2005/110220	11/2005
WO	WO 94/20051	9/1994	WO	WO 2005/118040	12/2005
WO	WO 95/02428	1/1995	WO	WO 2005/123166	12/2005
WO	WO 96/17643	6/1996	WO	WO 2006/000046	1/2006
WO	WO 96/25983	8/1996	WO	WO 2006/014630	2/2006
WO	WO 96/28207	9/1996	WO	WO 2006/052653	5/2006
WO	WO 96/39206	12/1996	WO	WO 2006/069345	6/2006
WO	WO 96/40370 A1	12/1996	WO	WO 2006/069415	7/2006
WO	WO 97/00092	1/1997	WO	WO 2006/074513	7/2006
WO	WO 97/07847	3/1997	WO	WO 2006/074515	7/2006
WO	WO 97/09090	3/1997	WO	WO 2006/074516	7/2006
WO	WO 97/20597 A1	6/1997	WO	WO 2006/074514	7/2006
			WO	WO 2006/099658	9/2006
			WO	WO 2006/102707	10/2006
			WO	WO 2006/130903	12/2006

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO 2006/138416	12/2006
WO	WO 2007/009182	1/2007
WO	WO 2007/041751	4/2007
WO	WO 2007/041786	4/2007
WO	WO 2007/048174	5/2007
WO	WO 2007/053878	5/2007
WO	WO 2007/143772	12/2007
WO	WO 2007/143792	12/2007
WO	WO 2007/145534	12/2007
WO	WO 2007/147088 A2	12/2007
WO	WO 2008/011682	1/2008
WO	WO 2008/011683	1/2008
WO	WO 2008/040050	4/2008
WO	WO 2008/058330 A1	5/2008
WO	WO 2008/070929	6/2008
WO	WO 2009/026627	3/2009
WO	WO 2009/052560	4/2009
WO	WO 2009/062265	5/2009
WO	WO 2009/108994	9/2009
WO	WO 2009/108995	9/2009
WO	WO 2009/109004	9/2009
WO	WO 2010/028425	3/2010
WO	WO 2010/066004	6/2010
WO	WO 2011/060479	5/2011
WO	WO 2013/057647	4/2013
WO	WO 2013/061260	5/2013

OTHER PUBLICATIONS

Notice of Opposition to Grant of Patent (Section 21) to New Zealand Patent Application No. 607032, filed Sep. 1, 2014, 7 pages.

Notice of Opposition to Grant of Patent (Section 21) to New Zealand Patent Application No. 622665, filed Sep. 1, 2014, 7 pages.

Notice of Opposition to Grant of Patent (Section 21) to New Zealand Patent Application No. 622666, filed Sep. 1, 2014, 7 pages.

Notice of Opposition to Grant of Patent (Section 21) to New Zealand Patent Application No. 622670, filed Sep. 1, 2014, 7 pages.

Application Under Regulation 168 for Extension of Time in New Zealand Patent Application Nos. 607032, 622666, 622670 and 622665, filed Sep. 1, 2014, 2 pages.

Amended Notice of Opposition to Grant of Patent filed by Fisher & Paykel Healthcare Limited in New Zealand Patent Application No. 622665 and Statement of Case filed on Oct. 30, 2014 (27 pages).

Amended Notice of Opposition to Grant of Patent filed by Fisher & Paykel Healthcare Limited in New Zealand Patent Application No. 622670 and Statement of Case filed on Oct. 30, 2014 (27 pages).

Amended Notice of Opposition to Grant of Patent filed by Fisher & Paykel Healthcare Limited in New Zealand Patent Application No. 607032 and Statement of Case filed on Oct. 30, 2014 (27 pages).

Amended Notice of Opposition to Grant of Patent filed by Fisher & Paykel Healthcare Limited in New Zealand Patent Application No. 622666 and Statement of Case filed on Oct. 30, 2014 (26 pages).

First Examination Report mailed Oct. 24, 2014 in New Zealand Application No. 701183 (2 pages).

First Examination Report mailed Oct. 21, 2014 in New Zealand Application No. 701136 (1 page).

Notification of the Fourth Office Action issued Oct. 17, 2014 in Chinese Application No. 200980116004.3, with English Translation (16 pages).

Office Action issued in corresponding U.S. Appl. No. 13/747,701 dated Sep. 17, 2014.

U.S. Appl. No. 13/834,189, filed Mar. 2013, Hitchcock et al.

U.S. Appl. No. 13/870,678, filed Apr. 2013, Kwok et al.

Adam J. Singer MD et al. "The Cyanoacrylate Topical Skin Adhesives," American Journal of Emergency Medicine, vol. 26, 2008, pp. 490-496.

Australian Appln. No. 2005253641—Examiner's First Report, dated Apr. 20, 2010.

Australian Appln. No. 2005253641—Examiner's Report, dated Aug. 18, 2011.

Australian Appln. No. 2006206040—Examination Report, dated Jun. 27, 2012.

Australian Appln. No. 2010251884—Examination Report, dated Jul. 27, 2012.

Australian Appln. No. PCT/AU2009/000214—International Search Report, dated May 18, 2009.

Chinese Appln. No. 200480011911.9—Office Action (w/English translation), dated Jun. 24, 2010.

Chinese Appln. No. 200580020203.6—Office Action (w/English translation), dated Jun. 1, 2010.

Chinese Appln. No. 200580020203.6—Office Action (w/English translation), dated Jul. 6, 2011.

Chinese Appln. No. 200580020203.6—Office Action (w/English translation), dated Dec. 23, 2011.

Chinese Appln. No. 200580020203.6—Office Action (w/English translation), dated Apr. 18, 2012.

Chinese Appln. No. 200680002169.4—Office Action (w/English translation), dated Mar. 23, 2010.

Chinese Appln. No. 200680002169.4—Third Office Action (w/English translation), dated Nov. 11, 2010.

Chinese Appln. No. 200810109270.0—Office Action (w/English translation), dated Oct. 19, 2011.

Chinese Appln. No. 200810109270.0—Office Action (w/English translation), dated Jun. 27, 2012.

Chinese Appln. No. 200910223650.1—Office Action (w/English translation), dated Mar. 29, 2012.

Chinese Appln. No. 201010000226.3—Office Action (w/English translation), dated Apr. 26, 2012.

Chinese Appln. No. 201010517066.X—Office Action (w/English translation), dated Nov. 10, 2011.

ComfortLite™, Respironics, <http://comfortlite.respironics.com>, before applicants' filing date.

ComfortLite™ 2, Respironics, <http://comfortlite2.respironics.com>, before applicants' filing date.

"Ear Loop Face Mask", before applicants' filing date.

European Appln. No. EP 01944732.5—Office Action, dated Nov. 27, 2009.

European Appln. No. EP 02714190.2—Search Report, dated Jul. 11, 2006.

European Appln. No. EP 03793493.2—Supplementary Search Report, dated Dec. 2, 2009.

European Appln. No. EP 03793493.2—Office Action, dated Mar. 18, 2011.

European Appln. No. EP 03810331.3—Supplementary Search Report, dated Dec. 18, 2009.

European Appln. No. EP 04730413.4—Supplementary Search Report, dated Sep. 29, 2009.

European Appln. No. EP 05749447.8—Supplementary Search Report, dated Dec. 8, 2009.

European Appln. No. EP 04802114.1—Supplementary Search Report, dated Apr. 27, 2009.

European Appln. No. EP 04802133.1—Supplementary Search Report, dated Sep. 8, 2009.

European Appln. No. EP 04802133.1—Office Action, dated Dec. 22, 2009.

European Appln. No. EP 05746824.1—Supplementary Search Report, dated Dec. 17, 2009.

European Appln. No. EP 06704287.9—Supplementary Search Report, dated Oct. 6, 2009.

European Appln. No. EP 06704287.9—Office Action, dated Jul. 18, 2011.

European Appln. No. EP 07784697.0—Search Report, dated Jul. 27, 2009.

European Appln. No. EP 07845378.4—Search Report, dated Dec. 1, 2009.

European Appln. No. EP 08154854.7—Extended Search Report, dated Nov. 27, 2008.

European Appln. No. EP 08154854.7—Examination Report, dated Jul. 1, 2011.

European Appln. No. EP 08161249.1—Extended Search Report, dated Mar. 19, 2009.

European Appln. No. EP 08161868.8—Search Report, dated Sep. 23, 2008.

(56)

References Cited**OTHER PUBLICATIONS**

- European Appln. No. EP 09003544.5—Search Report, dated Jun. 2, 2009.
- European Appln. No. EP 09161984.1—Extended Search Report, dated Sep. 3, 2009.
- European Appln. No. EP 09178736.6—Search Report, dated Apr. 19, 2010.
- European Appln. No. EP 10181516.5—Search Report, dated Jun. 13, 2012.
- European Appln. No. EP 10182015.7—Search Report, dated Jun. 15, 2012.
- European Appln. No. EP 11174401.7—Search Report, dated Oct. 20, 2011.
- European Appln. No. EP 11174407.4—Extended Search Report, dated Oct. 20, 2011.
- European Appln. No. EP 12154923.2—Extended Search Report, dated Jun. 1, 2012.
- European Appln. No. EP 12154926.5—Extended Search Report, dated Jun. 6, 2012.
- European Appln. No. EP 12165749.8—Extended Search Report, dated Oct. 10, 2012.
- European Appln. No. EP 12165751.4—Extended Search Report, dated Oct. 8, 2012.
- Fisher and Paykel Col.—Product Family—<http://www.fphcare.com/osa/products.asp/>, before applicants' filing date.
- German Patent No. 101 51 984—Decision from Opposition hearing by Weinmann (w/English translation), dated Dec. 6, 2007.
- Hans Rudolph, Inc.—Mask Products—<http://www.rudolphkc.com/products.php?category=MASKS>, before applicants' filing date.
- "If You Hate CPAP! You Need CPAP Pro ®," www.cpapro.com, before applicants' filing date.
- Japanese Appln. No. 2003-537718—Office Action (w/English translation), dated Oct. 7, 2008.
- Japanese Appln. No. 2003-559587—Office Action (w/English translation), dated Mar. 17, 2009.
- Japanese Appln. No. 2005-004072—Office Action (w/English translation), dated Sep. 24, 2009.
- Japanese Appln. No. 2005-337371—Reasons for Rejection (w/English translation), dated Feb. 22, 2011.
- Japanese Appln. No. 2007-515732—Office Action (w/English translation), dated Aug. 16, 2011.
- Japanese Appln. No. 2005-337371—Final Office Action (w/English translation), dated Jan. 31, 2012.
- Japanese Appln. No. 2006-504029—Office A545843ction (w/English translation), dated Nov. 10, 2009.
- Japanese Appln. No. 2006-545843—Notice of Reasons for Rejection (w/English translation), dated Jun. 7, 2011.
- Japanese Appln. No. 2007-515732—Office Action (w/English translation), dated Aug. 24, 2010.
- Japanese Appln. No. 2007-515732—Office Action (w/English translation), dated Jun. 12, 2012.
- Japanese Appln. No. 2007-550636—Office Action (w/English translation), dated Mar. 18, 2011.
- Japanese Appln. No. 2007-550636—Office Action (w/English translation), dated Mar. 21, 2012.
- Japanese Appln. No. 2007-550636—Notice of Allowance, dated Jul. 10, 2012.
- Japanese Appln. No. 2009-140433—Office Action (w/English translation), dated Aug. 20, 2011.
- Japanese Appln. No. 2009-140433—Notice of Allowance, dated Sep. 4, 2012.
- Japanese Appln. No. 2010-195597—Office Action (w/English translation), dated Jun. 12, 2012.
- Japanese Appln. No. 2010-214485—Office Action (w/English translation), dated Jun. 12, 2012.
- Japanese Appln. No. 2010-268127—Notice of Reasons for Rejection (w/English translation), dated Jul. 10, 2012.
- Japanese Appln. No. 2011-038110—Office Action (w/English translation), dated Aug. 14, 2012.
- Japanese Appln. No. S52-164619—English translation of Figure 1, Dec. 1977.
- Joel W. Beam, "Tissue Adhesives for Simple Traumatic Lacerations," *Journal of Athletic Training*, 2008, vol. 43, No. 2, pp. 222-224.
- JP 11-000397A Machine Translation, provided by the Japanese Patent Office, Jan. 6, 2009, full document.
- Laurent Brochard, "Pressure Support Ventilation," Chapter 9, Part IV—Conventional Methods of Ventilator Support, pp. 239-257, 1994.
- Mask 1 Photographs, Respiroics Inc., Reusable Full Mask (small) Part #452033 Lot #951108, before applicants' filing date.
- Mask 2 Photographs, Puritan—Bennett, Adam Curcuit, Shell Part #231700, Swivel Part #616329-00, Pillows (medium) Part #616324, before applicants' filing date.
- Mask 3 Photographs, DeVilbiss Healthcare Inc., Devilbiss Seal-Ring and CPAP Mask Kit (medium), Part #73510-669, before applicants' filing date.
- Mask 4 Photographs, Respiroics Inc., Monarch Mini Mask with Pressure Port, Part #572004, Monarch Headgear, Part #572011, before applicants' filing date.
- Mask 5 Photographs, Healthdyne Technologies, Nasal CPAP Mask (medium narrow), Part #702510, before applicants' filing date.
- Mask 6 Photographs, Healthdyne Technologies, Soft Series Nasal CPAP Mask, Part #702020, before applicants' filing date.
- Mask 7 Photographs, DeVilbiss Healthcare Inc., Small Mask and Seal Rings, Part #73510-668, before applicants' filing date.
- Mask 8 Photographs, Respiroics Inc., Reusable Contour Mask (medium), Part #302180, before applicants' filing date.
- Mask 9 Photographs, Healthdyne Technologies, Healthdyne Large Headgear, before applicants' filing date.
- Mask 14 Photographs, King System, before applicants' filing date.
- Mask 10 Photographs, Respiroics Inc., Soft Cap (medium), Part #302142, before applicants' filing date.
- Mask 11 Photographs, Weinmann: Hamburg, Nasalmaskensystem mit Schalldämpfer (medium), Part #WN 23105, before applicants' filing date.
- Mask 12 Photographs, Life Care, before applicants' filing date.
- Mask 13 Photographs, Healthdyne Technologies, before applicants' filing date.
- Mask 15 Photographs, Respiroics Inc., Pediatric Mask, before applicants' filing date.
- Mask 16 Photographs, Hans Rudolph Inc., Hans Rudolph Silicone Rubber Face Mask/8900, before applicants' filing date.
- McPherson et al., "Respiratory Therapy Equipment," Chapter 8, Third Edition, Introduction to Ventilators, pp. 230-253, 1985.
- Merriam-Webster Online Dictionary definition of moveable from the 14th century, before applicants' filing date.
- New Zealand Appln. No. 2003275762—Examiner's Report No. 3, dated Nov. 18, 2009.
- New Zealand Appln. No. 539836—Examination Report, dated Aug. 25, 2005.
- New Zealand Appln. No. 564877—Examination Report, dated Dec. 2, 2009.
- New Zealand Appln. No. 567375—Examination Report, dated Nov. 17, 2009.
- New Zealand Appln. No. 587344—Examination Report, dated Jan. 19, 2012.
- New Zealand Appln. No. 587344—Examination Report, dated Aug. 3, 2012.
- New Zealand Appln. No. 587820—Examination Report, dated Sep. 13, 2010.
- New Zealand Appln. No. 597552—Examination Report, dated Jan. 19, 2012.
- New Zealand Appln. No. 597689—Examination Report, dated Jan. 25, 2012.
- PCT/AU2003/001163—International Search Report, dated Nov. 4, 2003.
- PCT/AU2003/001471—International Search Report, dated Feb. 12, 2004.
- PCT/AU2004/000563—International Search Report, dated Jun. 23, 2004.
- PCT/AU2004/001760—International Preliminary Report on Patentability, dated Jul. 3, 2006.

(56)

References Cited**OTHER PUBLICATIONS**

PCT/AU2004/001760—International Search Report, dated Jan. 12, 2005.

PCT/AU2004/001813—International Preliminary Report on Patentability, dated Jul. 3, 2006.

PCT/AU2004/001813—International Search Report, dated Mar. 7, 2005.

PCT/AU2004/001832—International Preliminary Report on Patentability, dated Jul. 3, 2006.

PCT/AU2004/001832—International Search Report, dated Mar. 24, 2005.

PCT/AU2005/000803—International Search Report, dated Jun. 30, 2005.

PCT/AU2005/000850—International Preliminary Report on Patentability, dated Dec. 20, 2006.

PCT/AU2005/000850—International Search Report, dated Aug. 12, 2005.

PCT/AU2006/000032—International Preliminary Report on Patentability, dated Jul. 17, 2007.

PCT/AU2006/000032—International Search Report, dated May 15, 2006.

PCT/AU2006/000770—International Search Report, dated Aug. 3, 2006.

PCT/AU2007/001936—International Search Report, dated Mar. 4, 2008.

PCT/AU2006/001570—International Search Report, dated Jan. 5, 2007.

PCT/AU2007/001051—International Search Report, dated Nov. 5, 2007.

PCT/AU2007/001052—International Search Report, dated Oct. 9, 2007.

PCT/AU2007/001456—International Search Report, dated Dec. 12, 2007.

PCT/AU2009/000240—International Search Report, dated May 21, 2009.

PCT/AU2009/000262—International Search Report, dated Jun. 9, 2009.

PCT/AU2009/001102—International Search Report, dated Dec. 11, 2009.

PCT/AU2009/001144—International Search Report, dated Dec. 8, 2009.

PCT/AU2010/000657—International Search Report, dated Sep. 9, 2010.

Product Brochure for ResMed “Sullivan® Mirage™—The Mirage is Real. A Perfect Fit—First Time,” © 1997 ResMed Limited, 4 pages.

Product Brochure for ResMed “Sullivan® Mirage™—The Mirage is Real. A Perfect Fit—First Time,” © 1998 ResMed Limited, 4 pages.

ResMed Co.—Mask Products—<http://resmed.com/portal/site/ResMedUS/index.jsp?>, before applicants’ filing date.

ResMed Ltd., “Improving patient compliance with The ResMed Range of Mask Systems The Ultimate Interface for CPAP treatment,” before applicants’ filing date, 4 pages.

Respironics Co.—Mask Family—<http://maskfamily.respironics.com/>, before Applicant’s filing date.

SNAPP NASAL INTERFACE, Tiara Medical Systems, Inc.—http://tiaramed.com/asp_shops/shopdisplayproducts.asp?id=109&cat=SNAPP%2A+Nasal+Interface, before applicants’ filing date.

“Somnomask” brochure, 1999 along with various invoices relating to the “Somnomask”.

Somnotron CPAP—Great WM 2300 Instruction Manual, Weinmann Hamburg, 1991, 11 pages.

Subbu Venkatraman et al., “Review Skin Adhesives and Skin Adhesion I. Transdermal Drug Delivery Systems,” *Biomaterials*, vol. 19, 1998, pp. 1119-1136.

The ResMed Range of Mask Systems, product brochure, Nov. 1995, 4 pages.

Unsolicited email from Elson Silva, PhD, dated Mar. 28, 2008, “Requesting IDS of U.S. Pat. No. 6,766,817 for patents on fluids moving on porosity by Unsaturated Hydraulic Flow,” (email provided in both HTML and plain text format).

Photo of Weinmann Mask (manufactured 1991).

Photographs of Weinmann Mask, acquired prior to 1998, 7 pages.

U.S. Appl. No. 12/083,779—Office Action including PTO-892 listings, dated Feb. 17, 2012.

U.S. Appl. No. 12/083,779—Office Action including PTO-892 listings, dated Sep. 28, 2012.

U.S. Appl. No. 60/424,686, filed Nov. 8, 2002 (expired).

U.S. Appl. No. 60/483,622, filed Jul. 1, 2003 (expired).

U.S. Appl. No. 60/533,214, filed Dec. 31, 2003 (expired).

U.S. Appl. No. 60/634,802, filed Dec. 10, 2004 (expired).

U.S. Appl. No. 60/835,442, filed Aug. 4, 2006 (expired).

U.S. Appl. No. 60/643,121, filed Jan. 12, 2005 (expired).

U.S. Appl. No. 60/645,672, filed Jan. 21, 2005 (expired).

U.S. Appl. No. 60/795,615, filed Apr. 28, 2006 (expired).

U.S. Appl. No. 60/833,841, filed Jul. 28, 2006 (expired).

U.S. Appl. No. 60/852,649, filed Oct. 19, 2006 (expired).

U.S. Appl. No. 60/874,968, filed Dec. 15, 2006 (expired).

U.S. Appl. No. 60/907,856, filed Apr. 19, 2007 (expired).

U.S. Appl. No. 60/924,241, filed May 4, 2007 (expired).

U.S. Appl. No. 60/929,393, filed Jun. 25, 2007 (expired).

U.S. Appl. No. 60/935,179, filed Jul. 30, 2007 (expired).

U.S. Appl. No. 60/935,336, filed Aug. 8, 2007 (expired).

U.S. Appl. No. 60/996,160, filed Nov. 5, 2007 (expired).

U.S. Appl. No. 61/006,409, filed Jan. 11, 2008 (expired).

U.S. Appl. No. 61/064,818, filed Mar. 28, 2008 (expired).

U.S. Appl. No. 61/071,512, filed May 2, 2008 (expired).

U.S. Appl. No. 61/213,326, filed May 29, 2009 (expired).

U.S. Appl. No. 61/222,711, filed Jul. 2, 2009 (expired).

U.S. Appl. No. 61/263,175, filed Nov. 20, 2009 (expired).

U.S. Appl. No. 61/272,162, filed Aug. 25, 2009 (expired).

U.S. Appl. No. 61/272,250, filed Sep. 4, 2009 (expired).

U.S. Appl. No. 12/230,120, filed Aug. 8, 2008 (corresponds to JP 2009-0050156, Feb. 2009).

Webster’s New World Dictionary, Third College Edition 1988, definition for engaged and flexible, before applicants’ filing date.

Webster’s Third New International Dictionary, 1993, Dictionary definition for adjustable, bendable, and mild steel, before applicants’ filing date.

Notification of the First Office Action and English translation, for corresponding Chinese Application No. 200980116004.3, issued Dec. 24, 2012, 12 pages.

Notice of Reasons for Rejection and English Translation for corresponding JP Application No. 2010-548986, dated Apr. 16, 2003, 5 pages.

First Examination Report for corresponding NZ Application No. 607032, dated Feb. 18, 2013, 2 pages.

Patent Examination Report No. 1 for corresponding AU Application No. 2009221630, dated Mar. 21, 2013, 3 pages.

Office Action issued Apr. 4, 2013 in U.S. Appl. No. 13/747,772, including PTO-892.

Office Action issued Apr. 8, 2013 in U.S. Appl. No. 13/747,701, including PTO-892.

Notice of Allowance issued Mar. 28, 2013 in U.S. Appl. No. 12/736,024.

Notification of the Second Office Action and English Translation for corresponding Chinese Application No. 200980116004.3, issued Sep. 11, 2013, 14 pages.

European Search Report for corresponding European Application No. 09716457.8, mailed Jan. 31, 2014, 5 pages.

Australian Patent Examination Report No. 2 for corresponding Australian Application No. 2009221630, issued Feb. 25, 2014, 3 pages.

European Search Report for corresponding European Application No. 13197251.5, mailed Feb. 19, 2014, 6 pages.

Notice of Reasons for Rejection and English Translation for corresponding Japanese Application No. 2010-548986, mailed Mar. 3, 2014, 5 pages.

Third Office Action issued in Chinese Application No. 200980116004.3 dated Apr. 8, 2014 (with translation).

New Zealand First Examination Report for Application No. 624599 dated May 13, 2014 (2 pages).

6 photos of ResMed S8 Escape flow generator tub and liner, the tub and liner are joined by a chemical bond resulting from co-moulding.

(56)

References Cited

OTHER PUBLICATIONS

Japanese Office Action mailed Dec. 1, 2014 in Japanese Application No. 2010-548986, with English Translation (8 pages).
Communication Pursuant to Article 94(3) EPC mailed Feb. 11, 2015 in European Application No. 13 197 251.5 (4 pages).
Extension of Time Granted (1 page) mailed Mar. 2, 2015 in New Zealand Application No. 701136, together with a Notice of Opposition to Grant of Patent (Section 21) (8 pages).
Extension of Time Granted (1 page) mailed Mar. 2, 2015 in New Zealand Application No. 701183, together with a Notice of Opposition to Grant of Patent (Section 21) (8 pages).
Deadline for Counterstatement (1 page) mailed Mar. 27, 2015 in New Zealand Application No. 624599, together with Amended Notice of Opposition to Grant of Patent (Section 21) (9 pages) and Statement of Case (29 pages).
Statutory Declaration of Christopher Earl Nightingale executed Apr. 17, 2015 for submission in the Opposition of Australian Application No. 2009221630 (1 page).
Statutory Declaration of Alistair Edwin McAuley executed Apr. 9, 2015 for submission in the Opposition of Australian Application No. 2009221630 (39 pages).
Second Statutory Declaration of Alistair Edwin McAuley executed Apr. 14, 2015 for submission in the Opposition of Australian Application No. 2009221630 (6 pages).
Third Statutory Declaration of Alistair Edwin McAuley executed Apr. 17, 2015 for submission in the Opposition of Australian Application No. 2009221630 (11 pages).
Statutory Declaration of Troy Alan Baker executed Apr. 16, 2015 for submission in the Opposition of Australian Application No. 2009221630 (36 pages).
Statutory Declaration of Dr. David Maurice Rapoport executed Apr. 2, 2015 for submission in the Opposition of Australian Application No. 2009221630 (45 pages).

Statement of Case dated Apr. 28, 2015 and filed by Fisher & Paykel Healthcare Limited in New Zealand Opposition No. 701136 (14 pages).
Statement of Case dated Apr. 28, 2015 and filed by Fisher & Paykel Healthcare Limited in New Zealand Opposition No. 701183 (13 pages).
Communication mailed Jan. 5, 2015 (Extension of Time Granted), with Notice of Opposition filed Dec. 23, 2014, in New Zealand Application No. 624599 (9 pages).
Extended European Search Report mailed Jan. 15, 2015 in European Application No. 14182823.6 (6 pages).
IP Australian Official Receipt dated Jan. 19, 2015, with Statement of Grounds and Particulars, filed in Australian Application No. 2009221630 (21 pages).
Proceeding Correspondence mailed Jun. 17, 2015 in New Zealand Appln. No. 622670 (2 pages).
Proceeding Correspondence mailed Jun. 17, 2015 in New Zealand Appln. No. 607032 (2 pages).
Affirmation of Chun Cui executed Jun. 12, 2015 for submission in the Opposition of New Zealand Application Nos. 607032 (51 pages).
Statutory Declaration of Troy Alan Baker executed Apr. 16, 2015 for submission in the Opposition of New Zealand Application Nos. 607032, 622666 and 622670 (36 pages).
Statutory Declaration of Dr. David Maurice Rapoport executed Apr. 2, 2015 for submission in the Opposition of New Zealand Application Nos. 607032, 622666 and 622670 (46 pages).
Statutory Declaration of Alistair Edwin McAuley executed Apr. 9, 2015 for submission in the Opposition of New Zealand Application Nos. 607032, 622666 and 622670 (38 pages).
Second Statutory Declaration of Alistair Edwin McAuley executed Apr. 14, 2015 for submission in the Opposition of New Zealand Application Nos. 607032, 622666 and 622670 (3 pages).
Patent Examination Report No. 1 mailed May 29, 2015 in Australian Application No. 2014218465 (8 pages).

* cited by examiner




Fig. 1




Fig. 1B

Fig. 1C





Fig. 1D






Fig. 1E




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 8B




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18-1




Fig. 18-2




Fig. 19-1




Fig. 19-2




Fig. 19-3




Fig. 19-4






Fig. 20






Fig. 23




Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 29




Fig. 30




Fig. 31-1




Fig. 31-2




Fig. 31-3




Fig. 31-5




Fig. 31-4




Fig. 32-1




Fig. 32-2




Fig. 32-3




Fig. 33




Fig. 34




Fig. 35-1




Fig. 35-2




Fig. 35-3




Fig. 36




Fig. 37-1




Fig. 37-2




Fig. 37-3




Fig. 38-1




Fig. 38-2




Fig. 38-3




Fig. 38-4




Fig. 38-5




Fig. 39-1




Fig. 39-2




Fig. 39-3




Fig. 39-4




Fig. 39-5




Fig. 39-6




Fig. 40-1




Fig. 40-2




Fig. 40-3




Fig. 40-4




Fig. 40-5




Fig. 40-6




Fig. 40-7




Fig. 41-1




Fig. 41-2




Fig. 41-3




Fig. 41-4




Fig. 41-5




Fig. 41-6




Fig. 41-7




Fig. 41-8




Fig. 41-9




Fig. 41-10




Fig. 41-11






Fig. 41-12






Fig. 42-3




Fig. 42-4




Fig. 42-5




Fig. 42-6




Fig. 42-7




Fig. 43-1




Fig. 43-2




Fig. 43-3




Fig. 43-4




Fig. 44




Fig. 45

1

MASK SYSTEM**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. application Ser. No. 13/964,280, filed Aug. 12, 2013, which is a continuation of U.S. application Ser. No. 13/745,077, now U.S. Pat. No. 8,528,561, filed on Jan. 18, 2013, which is a continuation of U.S. application Ser. No. 12/736,024, now U.S. Pat. No. 8,550,084, filed on Sep. 2, 2010, which is the U.S. National Stage of PCT/AU2009/000241, filed Feb. 27, 2009, which claims benefit to U.S. Provisional Application Nos. 61/064,406, filed Mar. 4, 2008, 61/071,893, filed May 23, 2008, and 61/136,617, filed Sep. 19, 2008, each of which is incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

The present invention relates to a mask system used for treatment, e.g., of Sleep Disordered Breathing (SDB) with Continuous Positive Airway Pressure (CPAP) or Non-Invasive Positive Pressure Ventilation (NIPPV).

BACKGROUND OF THE INVENTION

Patient interfaces, such as a full-face or nasal mask systems, for use with blowers and flow generators in the treatment of sleep disordered breathing (SDB), typically include a soft face-contacting portion, such as a cushion, and a rigid or semi-rigid shell or frame. In use, the interface is held in a sealing position by headgear so as to enable a supply of air at positive pressure (e.g., 2-30 cm H₂O) to be delivered to the patient's airways.

One factor in the efficacy of therapy and compliance of patients with therapy is the comfort and fit of the patient interface.

The present invention provides alternative arrangements of mask systems to enhance the efficacy of therapy and compliance of patients with therapy.

SUMMARY OF THE INVENTION

One aspect of the invention relates to a mask system provided without a forehead support adapted to engage the patient's forehead.

Another aspect of the invention relates to a mask system including a frame and a shroud removably connected to the frame and adapted to attach headgear.

Another aspect of the invention relates to a mask system including a frame defining a breathing chamber, a cushion provided to the frame and adapted to form a seal with the patient's face, and a shroud provided to the frame. The shroud and the frame are co-molded with one another. The frame is constructed of a first, relatively soft, elastomeric material and the shroud is constructed of a second material that is more rigid than the frame. At least a portion of the frame includes a concertina section having a plurality of folds. Each of the folds has a side wall with the side walls of the folds becoming progressively longer away from the patient's face.

Another aspect of the invention relates to a cushion module including a frame defining a breathing chamber and a cushion adapted to form a seal with the patient's face. The frame and the cushion are co-molded with one another. The cushion is constructed of a first, relatively soft, elastomeric material and

2

the frame is constructed of a second material that is more rigid than the cushion. At least a portion of the frame includes a concertina section.

Another aspect of the invention relates to a method for constructing a cushion module. The method includes molding a first part of the cushion module with a first, relatively soft, elastomeric material, co-molding a second part of the cushion module to the first part with a second material that is more rigid than the first material, and molding at least a portion of the second part to include a concertina section.

Another aspect of the invention relates to a shroud for a mask system including a retaining portion structured to retain a frame, a pair of upper headgear connectors each including an elongated arm and a slot at the free end of the arm adapted to receive a headgear strap, and a pair of lower headgear connectors each adapted to attach to a headgear strap, wherein the retaining portion, the upper headgear connectors, and the lower headgear connectors are integrally formed as a one piece structure.

Another aspect of the invention relates to a mask system including a frame defining a breathing chamber, a cushion provided to the frame and adapted to form a seal with the patient's face, a shroud provided to the frame and adapted to attach headgear, and an elbow provided to the frame and adapted to be connected to an air delivery tube that delivers breathable gas to the patient. The shroud includes a retaining mechanism structured to establish a positive connection between the shroud and the frame.

Another aspect of the invention relates to a mask system including a frame defining a breathing chamber and a cushion provided to the frame. The cushion is adapted to engage at least a portion of the patient's face. The cushion includes a base wall connected to an undercushion layer and a membrane, wherein the membrane extends around the perimeter of the cushion and contacts the patient's face. The undercushion layer is positioned underneath the membrane and supports the membrane. The under cushion layer provides differential support to the membrane at predetermined regions of the face.

Another aspect of the invention relates to a mask assembly for use in medical applications having a top and bottom ends defined by its position relative to a patient's face, wherein the mask assembly is connected to a plurality of flexible straps, which are adapted to engage the patient's head. The flexible straps engage at least two elongated rigid arms integrally molded to a portion of the mask assembly, and wherein the elongated arms are molded to the mask assembly proximal to the top end of the mask assembly.

Another aspect of the invention relates to a mask assembly for use in medical applications including a main body connected to a cushion adapted to cover nose and/or mouth and wherein the mask assembly is attached by a force substantially perpendicular towards the face and wherein the force is approximately constant along the length of the mask and is balanced by a portion of the cushion engaging the patient's cheeks.

Another aspect of the invention relates to a cushion for use with a medical mask including an outer membrane layer adapted to sealably engage a face and an undercushion layer adapted to support the membrane layer. The membrane or undercushion layer includes a surface positioned between the two layers adapted to allow the layers to slide against the respective surface.

Another aspect of the invention relates to a mask system including a frame defining a breathing chamber, a cushion provided to the frame and adapted to form a seal with the patient's face, and a releasable shroud adapted to engage a

3

portion of the outer surface of the frame, wherein the shroud is connected to straps to position the mask system.

Another aspect of the invention relates to a mask assembly for use in medical applications including an upper end and a lower end wherein the upper end is adapted to cover the nose and the lower end is adapted to cover the mouth of a patient. The mask assembly includes no forehead support and includes two stiffened members attached to the upper end on opposed sides of the mask assembly, and wherein the stiffened members include a general curved shape and adapted to avoid covering the patient's field of vision.

Another aspect of the invention relates to a cushion for attaching to a medical mask, wherein the cushion is flexible and includes a membrane attached to the circumference of the cushion adapted to seal against the face of a patient, and at least one undercushion adapted to support the membrane and positioned underneath the membrane to prevent collapse of the membrane, in use. The membrane is softer than the undercushion. The undercushion in the regions of nasal bridge or chin is between 0 mm and 30 mm in height as measured between the base and the tip of the undercushion.

Another aspect of the invention relates to a mask assembly for use in medical applications including an upper end and a lower end wherein the upper end is adapted to cover the nose and the lower end is adapted to cover the mouth of a patient. The mask assembly includes no forehead support and includes two stiffened members attached to the upper end on opposed sides of the mask assembly, and wherein the stiffened members include a general curved shape and adapted to avoid covering the patient's field of vision.

In an alternative embodiment, the mask system may include a headgear connector or rigidizer structured to attach to the frame with a snap-fit, mechanical interlock, friction fit, and/or grommet arrangement (e.g., constructed of rubber).

In an alternative embodiment, the mask system may include headgear having an arrangement of straps constructed of silicone and/or Breath-O-Prene™ material.

Other aspects, features, and advantages of this invention will become apparent from the following detailed description when taken in conjunction with the accompanying drawings, which are a part of this disclosure and which illustrate, by way of example, principles of this invention.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings facilitate an understanding of the various embodiments of this invention. In such drawings:

FIG. 1 is a front perspective view of a mask system according to an embodiment of the present invention;

FIG. 1B is a perspective view showing the mask system of FIG. 1 with headgear positioned on a patient's head;

FIG. 1C is a cross-sectional view through the mask system of FIG. 1;

FIG. 1D is another cross-sectional view through the mask system of FIG. 1;

FIG. 1E is a side view of the mask system of FIG. 1;

FIG. 2 is a front perspective view showing the frame and cushion of the mask system of FIG. 1;

FIG. 3 is an exploded perspective view of the mask system of FIG. 1 showing the frame, cushion, shroud, and elbow;

FIG. 4 is another exploded perspective view of the mask system of FIG. 1 showing the frame, cushion, and shroud;

FIG. 5 is an exploded perspective view of the mask system of FIG. 1 showing the shroud and assembled frame/cushion;

FIG. 6 is a front perspective view showing the shroud of the mask system of FIG. 1;

4

FIG. 7 is a front perspective view showing the cushion of the mask system of FIG. 1;

FIG. 8 is a cross-sectional view showing a portion of the cushion of FIG. 7;

FIG. 8B is a cross-sectional view through nasal bridge and chin regions of the cushion of FIG. 7;

FIG. 9 is a plan view of headgear laid out flat according to an embodiment of the present invention;

FIG. 10 is a front perspective view of a mask system according to another embodiment of the present invention;

FIG. 11 is a front perspective view showing the frame of the mask system of FIG. 10;

FIG. 12 is a front view showing the frame of the mask system of FIG. 10;

FIG. 13 is a side view showing the frame of the mask system of FIG. 10;

FIG. 14 is a front perspective view showing the shroud of the mask system of FIG. 10;

FIG. 15 is a front view showing the shroud of the mask system of FIG. 10;

FIG. 16 is a side view showing the shroud of the mask system of FIG. 10;

FIG. 17 is a rear perspective view showing the shroud of the mask system of FIG. 10;

FIGS. 18-1 to 18-2 are cross-sectional views showing in sequential relation attachment of the shroud to the frame of the mask system of FIG. 10;

FIGS. 19-1 to 19-4 are cross-sectional views showing in sequential relation attachment of the shroud to the frame of the mask system of FIG. 10;

FIG. 20 is a perspective view showing an alternative arrangement for attaching the shroud to the frame;

FIG. 21 is a rear perspective view showing the shroud of the mask system of FIG. 10;

FIG. 22 is a cross-sectional view showing attachment of the shroud to the frame of the mask system of FIG. 10;

FIG. 23 is a cross-sectional view showing attachment of the shroud, frame, and elbow of the mask system of FIG. 10;

FIG. 24 is a cross-sectional view showing an alternative arrangement for attaching the shroud to the frame;

FIG. 25 is a front perspective view of a mask system according to another embodiment of the present invention;

FIG. 26 is a rear perspective view of the mask system of FIG. 25;

FIG. 27 is a front perspective view of a mask system according to another embodiment of the present invention;

FIG. 28 is an exploded view of the mask system shown in FIG. 27;

FIG. 29 is an enlarged front perspective view of the mask system shown in FIG. 17;

FIG. 30 is a side view of the mask system shown in FIG. 27;

FIGS. 31-1 is a rear view of a cushion according to an embodiment of the present invention;

FIG. 31-2 is a front view of the cushion shown in FIG. 31-1 with a partial cut-away;

FIG. 31-3 is a cross-section view through line 31-3-31-3 in FIG. 31-1;

FIG. 31-4 is a cross-section view through line 31-4-31-4 in FIG. 31-1;

FIG. 31-5 is a cross-section view through line 31-5-31-5 in FIG. 31-1;

FIGS. 32-1 to 32-3 illustrate top, front, and side views respectively of a concertina section according to an embodiment of the present invention;

FIG. 33 is a side view of a mask system according to a variation of the present invention;

5

FIG. 34 illustrates a cushion including a concertina section according to an embodiment of the present invention;

FIGS. 35-1 to 35-3 are front, side, and rear views of a mask system according to another embodiment of the present invention;

FIG. 36 is a perspective view of a shroud for a mask system according to an embodiment of the present invention;

FIGS. 37-1 to 37-3 are perspective, front, and side views of a mask system according to another embodiment of the present invention;

FIGS. 38-1 to 38-5 are perspective, front, top, side, and bottom views of a shroud of the mask system shown in FIGS. 37-1 to 37-3;

FIGS. 39-1 to 39-6 are perspective, front, side, bottom, and top views of a mask system according to another embodiment of the present invention;

FIGS. 40-1 and 40-2 are perspective and side views of a mask system according to another embodiment of the present invention;

FIG. 40-3 is a perspective view of the frame of the mask system shown in FIGS. 40-1 and 40-2;

FIGS. 40-4 and 40-5 illustrate a retaining member of the frame shown in FIG. 40-3;

FIGS. 40-6 and 40-7 illustrate a clip-on upper headgear connector of the mask system shown in FIGS. 40-1 and 40-2;

FIGS. 41-1 and 41-2 are rear and front perspective views of a mask system according to another embodiment of the present invention;

FIGS. 41-3 and 41-4 are exploded views of the mask system shown in FIGS. 41-1 and 41-2;

FIGS. 41-5 to 41-12 are various views of a clip-on upper headgear connector of the mask system shown in FIGS. 41-1 and 41-2;

FIG. 42-1 is a rear perspective view of a mask system according to another embodiment of the present invention;

FIG. 42-2 is an exploded view of the mask system shown in FIG. 42-1;

FIGS. 42-3 to 42-7 are various views of a clip-on upper headgear connector of the mask system shown in FIG. 42-1;

FIGS. 43-1 to 43-4 are perspective, side, front, and rear views of a mask system according to another embodiment of the present invention;

FIG. 44 illustrates a mask system according to another embodiment of the present invention; and

FIG. 45 illustrates a mask system according to another embodiment of the present invention.

DETAILED DESCRIPTION OF ILLUSTRATED EMBODIMENTS

The following description is provided in relation to several embodiments or examples which may share common characteristics and features. It is to be understood that one or more features of any one embodiment or example may be combinable with one or more features of the other embodiments or examples. In addition, any single feature or combination of features in any of the embodiments or examples may constitute additional embodiments or examples.

In this specification, the word “comprising” is to be understood in its “open” sense, that is, in the sense of “including”, and thus not limited to its “closed” sense, that is the sense of “consisting only of”. A corresponding meaning is to be attributed to the corresponding words “comprise”, “comprised” and “comprises” where they appear.

The term “air” will be taken to include breathable gases, for example air with supplemental oxygen.

6

The term “shroud” will be taken to include components that partially or fully cover a second component within the illustrated embodiments. In an embodiment, the shroud may include the component that partially covers or is mounted on the frame components of the illustrated embodiments.

The term “positive connection” will be taken to include connections between components of the illustrated embodiments wherein connectors mounted on respective components are adapted to engage each other respectively.

1. Mask System

Embodiments of the invention are directed towards a mask system provided without a forehead support adapted to engage the patient’s forehead. Such arrangement provides the mask system with a less obtrusive arrangement which does not significantly affect the patient’s field of view. Although the system is designed such that a forehead support is not required, such a forehead support can be added if desired.

As described in greater detail below, the mask system includes a frame, a cushion provided to the frame and adapted to form a seal with the patient’s face, a shroud provided to the frame and adapted to be connected to an air delivery tube that delivers breathable gas to the patient. Headgear may be removably attached to the shroud to maintain the mask system in a desired adjusted position on the patient’s face. The mask system is intended for use in positive pressure therapy for users with Obstructive Sleep Apnea (OSA) or another respiratory disorder.

While each embodiment below is described as including a full-face or oro-nasal interface type, each embodiment may be adapted for use with other suitable interface types. That is, the interface type is merely exemplary, and each embodiment may be adapted to include other interface types, e.g., nasal interface, nasal mask, nasal prongs, etc.

2. Stabilizing Mechanisms

The stabilizing mechanisms (e.g., frame, shroud, headgear with associated headgear vectors) of a mask system according to embodiments of the invention are structured to accommodate the elimination of a forehead support from a full-face type interface. For example, a forehead support typically eliminates rotation of the mask system in the sagittal and coronal planes, so the mask system and headgear according to embodiments of the invention are structured to take on these functions since there is no forehead support.

The headgear is connected to the top and bottom of the frame either directly or via the shroud, which shroud provides headgear connection points for headgear positioned and arranged to stably maintain the mask system in position on the patient’s face.

2.1 Frame

As shown in FIGS. 1, 1B-1E, and 2-5, the frame 1040 of the mask system 1010 is structured to maintain the cushion 1060, shroud 1020, and elbow 1070 in an operative position with respect to the patient’s face. The frame 1040 is constructed (e.g., injection molded) from a more rigid material (e.g., polyurethane) than the cushion 1060 (made of, e.g., silicone), however other materials may function likely as well (e.g., polycarbonate). In an embodiment, the frame has a general wall thickness of about 1-2 mm, e.g., 1.5 mm.

The frame 1040 defines a breathing chamber or cavity adapted to receive the patient’s nose and mouth and provide air communication to the patient. One or the lower portion of the frame 1040 includes an opening 1046 adapted to receive or otherwise communicate with the elbow 1070 (e.g., swivel elbow) and another or upper portion of the frame 1040 includes a vent arrangement 1076 for gas washout. In addition, the upper portion of the frame 1040 includes an inter-

7

facing structure **1048** adapted to interface or otherwise removably connect to the shroud **1020**.

FIGS. **27-30** shows a mask system **10** including a frame **40** with a cushion **44** that provides a sealing portion or sealing ring adapted to form a seal with the patient's nose and/or mouth. Also, the frame **40** includes an opening **46** that is adapted to communicate with the elbow **70**.

2.2 Shroud

As shown in FIGS. **1** and **3-6**, the shroud **1020** is connected to the frame **1040** and is structured to attach headgear to the mask system. In an embodiment, the shroud **1020** is constructed (e.g., injection molded) of a resilient material including but not limited to plastic or nylon (e.g., Nylon 12). However, the shroud may be constructed of other suitable materials, e.g., polycarbonate, polypropylene, thermoplastic elastomer (TPE), Pocan®, etc. In an embodiment, the shroud has a general wall thickness of about 1-2 mm, e.g., 1.3 mm.

The top end of the shroud **1020** is adapted to be positioned proximal to the nasal bridge region or nose of the patient and the bottom end is adapted to be positioned proximal to the mouth or chin of the patient. The top end includes an opening or vent receiving hole **1021** to accommodate the vent arrangement **1076** that protrudes from the frame **1040**, and the bottom end includes an opening or elbow hole **1032** to accommodate the elbow **1070** and elbow opening into the frame **1040** (e.g., shroud provides no contact with elbow when assembled).

Upper headgear connectors **1024** extend from each side of the top end, and lower headgear connectors **1025** extend from each side of the lower end. The headgear connectors **1024**, **1025** may be integrally molded or otherwise attached to the shroud.

2.2.1 Upper Headgear Connectors

Each upper headgear connector **1024** includes an elongated arm **1026** and a slot or receiving hole **1027** at the free end of the arm **1026** adapted to receive a respective headgear strap. In use, the arms **1026** extend around the face of the patient in a generally concave angle below the eyes of the patient so as to avoid the patient's field of view, i.e., direct headgear away from the patient's eyes. For example, as shown in FIG. **1E**, each arm **1026** may extend at an angle α between about 10-25° (e.g., 17°) with respect to horizontal. That is, each arm **1026** is suitably formed, shaped, or contoured to follow the contours of the patient's face and avoid line of sight in use. In an embodiment, the shape of the arms may be generally arcuate and adapted to extend in a direction across the cheek of the patient, while avoiding the eyes or limiting the field of vision. In an embodiment, the arms may be integrally molded to the shroud of the mask system. One possible advantage of molding the arms onto the shroud is that it greatly increases manufacturability and also the shroud may be easily replaced in the case of accidental breakage of the arms rather than replacing the complete mask system. Additionally, molding of the arms onto the shroud may greatly increase the strength of the connection and reduce or limit the actual likelihood of breakage of the arms.

In an embodiment, the arms **1026** are at least semi-rigid (e.g., relatively rigid) so as to prevent up and down movement or bending of the arms relative to the face of the patient. Thus, the arms **1026** may act as rigidizers to effectively act as a level arrangement and generate a mechanical advantage wherein the pressure or force applied to top end of the mask system is readjusted to a fulcrum point being about the center of balance between the top and bottom ends of the mask system. In an embodiment, the arms are attached to the highest possible point relative to the mask system to additionally stabilize the configuration. In an embodiment, the fulcrum point or

8

moment of pivoting is positioned between the upper and lower connection points of the straps, and wherein the design, angle, length and/or configuration of the arms **1026** may effectively adjust the fulcrum point. In the illustrated embodiment, the fulcrum point is shown to be between the vent arrangement and elbow of the mask system. Additionally, when positioned on the face, the mask system may have a fulcrum point around or about the region between the bottom of the patient's nose and lip area. This feature effectively stabilizes the mask system on the patient's face without the traditional need for a forehead support.

The net result of the arms **1026** mounted in a position extending from the top end of the mask system around the face of the patient is that the mask system is more stable and reduces the net torsional forces experienced about the x-axis **1001** (see FIG. **1**) for the mask system in use. Please note that the arms **1026** may be rigidly connected to the mask system in other suitable positions to generate a similar result.

In an embodiment, the arms **1026** may be used to stabilize the mask system by contacting the patient's face at the cheeks. A cheek pad may be provided to the inner surface of the arm to support the arm on the patient's cheek in use. Also, the arms **1026** may be enveloped in a soft fabric sleeve to act as additional padding against the cheeks of the patient. The soft fabric sleeve may be in the configuration of an elastic tube covering a portion of the arms **1026**.

2.2.2 Lower Headgear Connectors

Each lower headgear connector **1025** includes an abbreviated arm and a clip receptacle **1031** at the free end of the arm adapted to be removably interlocked with a headgear clip associated with a respective headgear strap. The clips allow for easier positioning or donning/removal of the mask system. In an embodiment, the abbreviated arms and clips are also relatively rigid so as to prevent lateral movement of the arms along the y-axis **1002**, relative to the mask system in use.

FIGS. **27-30** illustrate an exemplary headgear clip **33** adapted to be removably interlocked with a clip receptacle **31**. As best shown in FIG. **28**, each clip **33** includes two spring arms **35** adapted to interlock with the respective clip receptacle **31** with a snap-fit and a slot **37** adapted to receive a respective headgear strap in use.

2.2.3 Alternative Headgear Connectors

As shown in FIGS. **27-30**, the arm **26** may be removably coupled to the shroud, e.g., arm **26** includes clip structure adapted to removably interlock with a clip receptacle provided to the shroud. This arrangement allows different styles of upper and lower headgear connectors to be used with the shroud, e.g., arms for both upper and lower headgear connectors, clips for both upper and lower headgear connectors, different length arms for upper and lower headgear connectors, etc.

However, the shroud may provide other suitable arrangements for attaching headgear straps of headgear. Also, the shroud may include one or more additional components, e.g., forehead support.

2.2.4 Headgear Connector Positioning

In the embodiment of FIGS. **1-6**, the upper and lower headgear connectors **1024**, **1025** provide headgear connection points that are as far from each other as possible (i.e., top and bottom of frame) to allow for greater adjustability (e.g., allows adjustment at the top and bottom of the mask system) and stability (e.g., anchor points spread out around the mask system so more secure on the patient's face). Also, the upper headgear connectors are positioned as close to the top of the mask system as possible without obstructing the patient's eyes in use.

2.2.5 Separate Shroud

In the embodiment of FIGS. 1-6, the shroud **1020** is formed separately (e.g., molded) and attached to the frame **1040**. Such arrangement facilitates molding of the shroud, allows different materials to be used for the frame and shroud (e.g., frame can be semi-rigid or rigid for stability and shroud with headgear rigidizers can be flexible for adjustment, allows the shroud to hide elbow retention features around elbow/frame opening for retaining elbow to frame (e.g., provides visual shroud for aesthetics), allows frame to be free of lower clip receptacles, allows shroud to be used with different size frames, and allows the shroud to be designed or stylized to minimize obtrusiveness of the mask system. The separate shroud may also allow the headgear, frame, cushion, and/or elbow to be replaced or washed independently.

2.2.6 Sleeves

In an embodiment, soft fabric sleeves may be mounted on the upper and/or lower headgear connectors. For example, the sleeves may be elastic and adapted to slide over the arms of the headgear connectors to form a tight fit. In an embodiment, the sleeves form elastic tubes. The sleeves may be padded to increase the comfort of the mask system in use. The sleeves may be particularly useful where the arms of the headgear connectors contact the patient's skin, e.g., to protect the patient's skin from irritation.

2.2.7 Arm Extends Over the Patient's Ear

FIGS. 35-1 to 35-3 and 36 illustrate a shroud **220** for mask system **210** according to another embodiment of the present invention. The shroud **220** includes an annular retaining portion **222** structured to retain the frame **240** and upper and lower headgear connectors **224**, **225** on each side of the retaining portion **222**. In the illustrated embodiment, the shroud **220** is integrally formed in one piece (e.g., see FIG. 36).

In the illustrated embodiment, each upper headgear connector **224** includes an elongated arm **226** and a slot **227** at the free end of the arm **226** adapted to receive a respective rear strap **298** in use. As illustrated, the arm **226** is suitably contoured to extend along the cheeks and over the patient's ear just anterior of the patient's temple and retain the respective rear strap **298** in spaced relation over the patient's ear, e.g., to avoid the strap rubbing or irritating the patient's ear in use.

Also, each arm **226** is structured to extend along and engage an upper strap **292** of the headgear in use. As illustrated, each arm **226** is secured to the upper strap **292** to add rigidity to the strap and stabilize the mask system on the patient's face in use. In addition, the strap **292** provides padding to the arm **226** on the patient's face in use. In an embodiment, the upper strap **292** may be fixed to the arm **226** by gluing or stitching for example. Alternatively, the arms **226** may be encapsulated by or inserted into respective straps **292** so that the arms **226** are substantially not visible.

Each lower headgear connector **225** includes an abbreviated arm **228** with a slot **229** at the free end of the arm **229** adapted to receive a respective lower strap **294** in use. As illustrated, the arm **228** is suitably oriented to retain the respective lower strap **294** in spaced relation under the patient's ear, e.g., to avoid the strap rubbing or irritating the patient's ear in use.

In an embodiment, each arm may be attached to the upper end of the mask system and curves below the patient's field of vision or eyes and curves upwards at an angle between about 10 to 20 degrees away from the horizontal axis.

In an alternative embodiment, as shown in FIG. 36, each lower headgear connector **225** may include a clip receptacle **231** adapted to be removably interlocked with a headgear clip (not shown) associated with a respective lower strap **294**. In

an embodiment, the headgear clip receptacle and clip may be similar to that on ResMed's Mirage Liberty™ mask. Exemplary clip arrangements are disclosed in U.S. Patent Publication Nos. 2007/0144525 and 2006/0283461, each of which is incorporated herein by reference in its entirety.

2.2.8 Shroud without Upper Headgear Connector

FIGS. 37-1 to 37-3 illustrate a mask system **310** according to another embodiment of the present invention. As illustrated, the mask system **310** includes a shroud **320**, a frame **340**, a cushion **344**, and an elbow **370**.

As best shown in FIGS. 38-1 to 38-5, the shroud **320** includes an opening **322** structured to receive the elbow **370** and a headgear connector **325** on each side thereof. In the illustrated embodiment, each headgear connector **325** includes a clip receptacle **331** adapted to be removably interlocked with a headgear clip (not shown) associated with a respective lower headgear strap.

The frame **340** is removably attached to the shroud **320**, e.g., fingers and tabs **345** extending from opening **322** adapted to engage collar of frame **340**.

The frame **340** includes an upper headgear connector **324** on each upper side thereof. Each headgear connector **324** includes a clip retainer **333** adapted to be removably interlocked with a headgear clip (not shown) associated with a respective upper headgear strap.

FIGS. 39-1 to 39-6 illustrate an alternative version of the mask system **310**, which is indicated with similar reference numerals. As illustrated, the frame **340** is provided without upper headgear connectors, and the each clip receptacle **331** includes an alternative configuration (e.g., holes for snap-fit tabs on the clip). Also, the shroud **320** in FIGS. 39-1 to 39-6 includes support bars **329** structured to wrap around respective auxiliary ports **343**, while the shroud **320** in FIGS. 37-1 to 38-5 includes support bars **329** that extend in front of respective auxiliary ports **343**.

2.3 Headgear

Headgear may be removably attached to the headgear connectors **1024**, **1025** of the shroud **1020** to maintain the mask system **1010** in a desired position on the patient's face, e.g., see FIG. 1B.

As shown in FIG. 9, the headgear **1090** includes a pair of upper and lower straps **1092**, **1094** with the upper straps **1092** removably attached to respective upper headgear connectors **1024** and the lower straps **1094** removably attached to respective lower headgear connectors **1025**. The free end of each strap may include a Velcro® tab structured to engage the remainder of the strap to secure the strap in place. Such Velcro® attachment also allows adjustment of the length of the straps. However, the upper and lower headgear straps may be secured to the shroud in any other suitable manners, e.g., adjustable ladder-lock arrangement, etc.

The upper straps **1092** split at the crown of the patient's head to top straps **1096** (e.g., connected to one another by a buckle) adapted to pass over the top of the patient's head in use and rear straps **1098** adapted to pass behind the patient's head in use. In an embodiment, the headgear **1090** is structured to be self-supporting.

In FIG. 9, the top straps **1096** are adapted to be connected to one another by a buckle. In an alternative embodiment, as shown in FIG. 27-30, headgear **90** may include upper and lower straps **92**, **94**, top strap **96**, and rear strap **98**, with the top straps **96** integral with one another.

The upper straps **1092** are designed to adjust the position of the mask in a similar way that an adjustable forehead support would alter the position of the mask system, i.e., move the top of the mask system closer or further away from the patient's nasal bridge.

11

Without the forehead support, the headgear is connected at the top and bottom of the mask frame 1040 via the shroud 1020, and in order to avoid the eyes and ears, the arm 1026 of the upper headgear connector extends at an angle. In doing so, the headgear vectors V1 and V2 (see FIGS. 1 and 1B) are aligned such that the mask system may have a tendency to ride up the patient's face (i.e., upper headgear connectors position upper headgear vectors upwardly from horizontal and lower headgear connectors position lower headgear vectors generally horizontal). By splitting the upper headgear strap 1092 at the crown of the patient's head (i.e., top and rear straps 1096, 1098), the upper headgear vectors are realigned to prevent the mask system from sliding up the patient's face.

2.3.1 Headgear Adjustment

FIGS. 35-1 to 35-3 illustrate headgear 290 attached to the headgear connectors 224, 225 of the shroud 220 to maintain the mask system in a desired position on the patient's face.

In the illustrated embodiment, the headgear 290 includes a pair of upper or top straps 292, a pair of lower or bottom straps 294, and a pair of rear straps 298. In use, the upper straps 292 are secured to respective upper connectors or arms 226, the lower straps 294 are removably attached to respective lower connectors via slots 229/clip arrangement 231, and the rear straps 298 are removably attached to respective upper connectors via slots 227. The upper straps 292 may include upper strap portions adapted to pass over the top of the patient's head and couple to one another, e.g., via a headgear buckle or adjustable ladder-lock arrangement 299. In the illustrated embodiment, the lower straps 294 and rear straps 298 are formed in one piece.

This headgear arrangement allows adjustment to occur at three positions, i.e., upper straps 292 at the headgear buckle 299, lower straps 294 at the slot 229/clip 231 connection, and rear straps 298 at the slot 227 connection.

As illustrated, the free end of each strap may include a hook and loop tab 295 (e.g., Velcro®) structured to engage the remainder of the strap to removably secure the strap in place. Such hook and loop attachment also facilitates adjustment of the length of the straps.

In the illustrated embodiment, the lower straps 294 and rear straps 298 are adapted to join and pass behind the patient's head in use (e.g., see FIG. 35-3). As illustrated, the lower straps 294 join at an angle α (e.g., similar to the bottom strap in ResMed's Mirage Liberty mask) to prevent the strap from irritating the patient's neck and/or prevent movement of the strap due to movement of the patient's neck in use.

In an embodiment, the headgear may be similar to that for ResMed's Mirage Liberty mask, however the top straps have been modified and there is an added rigidizer system. The top straps may be similar to ResMed's Swift style headgear, with the rigidizers extending along the sides.

2.3.2 Alternative Headgear Material

FIGS. 43-1 to 43-4 illustrate a mask system 610 including a mask 615 and headgear 690 according to another embodiment of the present invention. In the illustrated embodiment, the headgear 690 includes an arrangement of straps wherein some of the straps are constructed of silicone and some of the straps are constructed of Breath-O-Prene™ material. However, the headgear may be constructed such that the straps are completely constructed of silicone or completely constructed of Breath-O-Prene™.

As illustrated, the lower strap portion 692 of the headgear is constructed of Breath-O-Prene™ and extends along the cheeks and around the back of the patient's head. The upper strap portion 694 of the headgear is constructed of silicone and includes side straps 694(1) that extend along the upper cheek and over the patient's ear, a top strap 694(2) that

12

extends over the top of the patient's head, rear straps 694(3) that extend behind the patient's head and connects to the lower strap portion 692 (see FIG. 43-4), and connecting portions 694(4) that extend from respective side straps 694(1) in front of the patient's ear and connect to the lower strap portion 692.

The headgear straps may be connected to the mask in any suitable manner. For example, in the illustrated embodiment, the lower strap portion 692 is connected to the mask by a headgear clip arrangement and the upper strap portion 694 is connected to the mask using an elongated buckle 695 with buckle portions on each end thereof.

In an embodiment, the headgear straps are arranged such that the force vectors applied by the headgear to the mask are substantially perpendicular to the mask and substantially parallel to one another (e.g., as shown by the arrows in FIG. 43-2). This arrangement enhances the mask seal as the headgear forces the mask directly into the patient's face.

3. Seal

The seal (i.e., cushion) of the mask system is structured to accommodate the elimination of a forehead support from a full-face type interface.

3.1 Cushion

As shown in FIGS. 1-5 and 7-8, the cushion 1060 is structured to interface with the frame 1040 and form a seal with the patient's nose and mouth in use. In the illustrated embodiment, the cushion is a full-face cushion adapted to engage the patient's face generally along nasal bridge, cheek, and lower lip/chin regions of the patient's face. However, other cushion interfaces are possible, e.g., nasal.

The cushion 1060 is structured to be more compliant or flexible (e.g., particularly in the nasal bridge region) to accommodate more movement due to loss of some stability without a forehead support.

The cushion 1060 is constructed of a soft and flexible biocompatible material, e.g., such as silicone. In the illustrated embodiment, the cushion 1060 includes a dual wall configuration wherein the cushion comprises an undercushion or support wall 1062 underneath a membrane 1064 as shown in FIG. 8.

The membrane 1064 is generally softer and less stiff than the undercushion 1062 and provides a seal against the patient's face in use. The membrane may be relatively thin to allow for wider fit range and better conformance to the patient's face in view of less mask stability with a forehead support. The undercushion is structured to generally support the membrane and prevents collapse of the membrane when the mask system is attached and tightened using the headgear.

The membrane 1064 is generally concave and curves inwards towards the breathing chamber. The undercushion 1062 may also curve inwardly but is generally shorter, thicker, and more rigid than the membrane.

In an embodiment, the undercushion 1062 at the regions of the nasal bridge and/or chin of the patient is shorter in height or completely absent and the height from the tip to base of the undercushion 1062 may be between about 0 mm and 30 mm. The membrane is generally longer than the undercushion 1062 at any given cross-section and may be between about 1 mm and 40 mm. For example, FIG. 8B illustrates a cross-section through nasal bridge and chin regions of the cushion to illustrate the membrane 1064 without an undercushion in these regions.

In an embodiment, the undercushion 1062 may only be provided in selected regions of the mask system, e.g., where the mask system is to be pushed away from the patient's face. Certain pre-determined regions of the patient's face may be preferably avoided for applying pressure by the tightening of

13

the headgear. In the illustrated embodiment, the nasal bridge and chin regions of the patient do not include an undercushion **1062**. In these regions, the undercushion is only provided along lateral sides of the cushion (e.g., see FIG. 7) which press against the cheeks of a patient so as to more evenly distribute the force vectors applied by the mask system in use. In an embodiment, the undercushion may be relatively stiff along the cheek regions because these points of contact are acting as anchor points, i.e., holds mask system in position to provide effective seal.

This configuration of avoiding the nasal bridge and chin of the patient may increase the comfort of the mask system for patients by reducing the pressure or force applied to sensitive areas or to protruding regions of the patient's face that experience relatively higher contact pressures. Additionally, this arrangement avoids the cushion pinching the nasal bridge of the patient when the mask system is adjusted. Additionally, the cushion of this embodiment may be noticeably softer in the regions of the nasal bridge and chin because of the absence of the undercushion.

In an embodiment, the undercushion may include a variable height, stiffness, and/or thickness to generate a variable softness in the aforementioned predetermined regions of the face that require lighter support.

In the illustrated embodiment, the cushion may be structured to seal lower down on the patient's nasal bridge and the eye sockets so that the cushion is less obtrusive.

In an embodiment, the cushion may be generally frosted except at patient contacting surfaces where it is polished. In an embodiment, the frosting of the cushion may reduce restriction between the face and membrane and/or the membrane and undercushion. The frosting allows the surface of the membrane and undercushion to slide against each other's respective surface without the same restriction of unfrosted silicone. This feature may also prevent or limit sticking of the membrane to the undercushion components and also may generally improve the overall comfort and sealing properties of the cushion. Additionally, the frosting of the cushion may be easier to manufacture and may lead to a reduction of costs of manufacturing. The cushion may be constructed of frosted silicone or other suitable materials.

3.2 Cushion Lower on Nasal Bridge

FIGS. **31-1** to **31-5** illustrate various views of a cushion **44** (e.g., constructed of silicone) according to an embodiment of the present invention. As illustrated, the cushion **44** includes a base wall **44(1)** provided to the frame, an undercushion layer (UCL) **44(2)** extending away from the base wall **44(1)**, and a membrane **44(3)** provided to substantially cover the UCL **44(2)** and provide a sealing structure. In the illustrated embodiment, the cushion **44** is structured to sit lower on the nasal bridge to reduce mask obtrusiveness and improve "line of sight" in use.

Also, as best shown in FIGS. **31-3** and **31-5**, the UCL **44(2)** design in the nasal bridge region is structured to provide improved stability across the nasal bridge in use. As shown in FIGS. **31-1** and **31-3**, the UCL is not provided in the lower lip/chin region. However, other arrangements of the UCL are possible, e.g., UCL around entire perimeter.

In an embodiment of the cushion shown in FIGS. **31-1** to **31-5**, **D1** may be about 15-20 mm, e.g., 18.2 mm, **D2** may be about 53-59 mm, e.g., 55.8 mm, **D3** may be about 88-93 mm, e.g., 90 mm, **D4** may be about 78-83 mm, e.g., 81.1, **D5** may be about 58-63 mm, e.g., 60 mm, **D6** may be about 95-100 mm, e.g., 98.1 mm, **D7** may be about 57-62 mm, e.g., 59.7 mm, **D8** may be about 77-82 mm, e.g., 79 mm, **D9** may be about 88-93 mm, e.g., 90.7 mm, **D10** may be about 30-35 mm, e.g., 33.1 mm, **D11** may be about 14-19 mm, e.g., 16.4

14

mm, **D12** may be about 8-13 mm, e.g., 9.6 mm, **D13** may be about 0.3-0.5 mm, e.g., 0.35 mm, **D14** may be about 0.4-0.6 mm, e.g., 0.5 mm, and **D15** may be about 0.3-0.5 mm, e.g., 0.4 mm. Although specific dimensions and ranges are indicated, it is to be understood that these dimensions and ranges are merely exemplary and other dimensions and ranges are possible depending on application. For example, the exemplary dimensions may vary by 10-20% or more or less depending on application.

3.3 Cushion Higher on Nasal Bridge

FIGS. **35-1** and **35-2** illustrate a full-face cushion **244** adapted to engage the patient's face generally along nasal bridge, cheek, and lower lip/chin regions of the patient's face. In this embodiment, the cushion **244** is structured such that it is positioned higher on the bridge of the nose for sealing and comfort (e.g., with respect to the cushion **44** described above). The cushion **244** may also be better for anthropometrics, i.e., the cushion will fit more people.

In an embodiment, the cushion **244** may include a concertina section as described below (e.g., in the nasal bridge region) to enhance the flexibility of the cushion in use.

3.4 Concertina Section

As best shown in FIGS. **30** and **33**, a concertina section **50** may be provided in a nasal bridge region of the cushion and/or frame. As illustrated, the concertina section **50** includes a bellows structure with one or more folds **52** that provide a higher degree of flexibility or increased movement. That is, the concertina section **50** provides a higher level of adaptability or flexibility to the nasal bridge region of the cushion/frame which is a more sensitive region of the patient's face in use. Moreover, the concertina section **50** provides increased movement without compromising seal.

FIGS. **32-1** to **32-3** illustrate various views of a concertina section **50** (isolated from the remainder of the cushion/frame) with one or more folds **52** according to an embodiment of the present invention. As best shown in FIG. **32-3**, the folds may have different lengths, depths, and/or contours with respect to one another to optimize the concertina effect, e.g., provide sufficient degree of movement without compromising seal. For example, as shown in FIG. **32-3**, each fold **52** includes a first side wall **52(1)** and a second side wall **52(2)** that interconnects adjacent side walls **52(1)**.

In the illustrated embodiment, the first side walls **52(1)** and/or the second side walls **52(2)** may become progressively longer away from the patient's face. For example, the first side wall **52(1)** and/or the second side wall **52(2)** adjacent patient's face, or the combination of side walls **52(1)** and **52(2)**, may have a length that is longer than and in some cases significantly longer than the adjacent side wall **52(1)** and/or **52(2)** (e.g., one side wall at least 25% greater than and up to 5x as long as the other side wall, e.g., 1x, 2x, 3x, or 4x).

The folds may be constructed and arranged to provide a predetermined order of movement or folding, e.g., folds structured to fold in a sequential or progressive manner wherein one fold collapses before an adjacent fold collapses. For example, upon application of force, the folds closest to the patient's face may fold or collapse before the folds furthest from the patient's face. Also, the folds may be constructed and arranged to provide various degrees of fold or collapse, e.g., folds may fold or collapse more than others.

In an embodiment of the concertina section shown in FIGS. **32-1** to **32-3**, **D1** may be about 50-60 mm, e.g., 55.7 mm, **D2** may be about 5-15 mm, e.g., 9.7 mm, and **D3** may be about 0.3-0.5 mm, e.g., 0.4 mm. Although specific dimensions and ranges are indicated, it is to be understood that these dimensions and ranges are merely exemplary and other dimensions and ranges are possible depending on application. For

15

example, the exemplary dimensions may vary by 10-20% or more or less depending on application.

It should be appreciated that a concertina section **50** may be provided in other regions of the cushion and/or frame, e.g., depending on patient comfort. For example, the concertina section **50** may be provided around the entire perimeter of the cushion and/or frame or may be provided in selected regions of the cushion and/or frame.

Also, the flexibility of the concertina section **50** may be varied and may be varied in different regions of the cushion and/or frame, e.g., depending on patient comfort. For example, the cushion and/or frame may include a concertina section in the nasal bridge region with a relatively high degree of flexibility and a concertina section in the lower lip/chin region with a relatively low degree of flexibility. The flexibility of the concertina section **50** may be varied by varying the number of folds **52** (e.g., 1-5 folds), the wall lengths, the wall thickness of the folds **52**, the depth of the folds **52**, etc.

As noted above, the cushion and frame may be co-molded of two parts with different materials/rigidities or may be integrally formed of the same material. In both embodiments, the concertina section may be provided in the frame and/or the cushion.

In FIGS. 27-30, the cushion **44** and frame **40** are co-molded of two parts with the concertina section **50** provided in the frame **40**. The frame **40** and cushion **44** include different rigidities in order to optimize the function of each part. For example, one part (i.e., cushion **44**) may be constructed of a relatively soft, supple material to optimize the sealing effect and the other part (i.e., frame **40**) may be constructed of a more rigid material to provide adequate support for the cushion while at the same time allowing a sufficient degree of movement to optimize the concertina effect. While the frame is more rigid than the cushion, the frame may be constructed of a flexible material to allow the concertina effect.

In FIG. 33, the frame **40** and cushion **44** are integrally formed in one piece with the concertina section **50** provided in the frame **40**. The material properties and/or dimensions may be selectively modified to optimize sealing and concertina effects.

For both embodiments of FIGS. 27-30 and 33, it should be appreciated that the concertina section may be alternatively provided in the cushion **44** or in both the frame **40** and cushion **44**. For example, FIG. 34 illustrates a concertina section **50** integrally formed with the cushion **44** in the nasal bridge region.

4. Elbow

As shown in FIG. 3, the elbow **1070** (e.g., constructed of a relatively hard material such as polycarbonate or polypropylene) includes a first end portion **1074(1)** and a second end portion **1074(2)**. The first end portion **1074(1)** provides an interfacing structure to interface or otherwise attach to the frame **1040**. The second end portion **1074(2)** is adapted to be connected to an air delivery tube.

4.1 Elbow Connection to Frame/Shroud

As shown in FIGS. 27-30, the shroud module **20** is structured to maintain the elbow module **70** in an operative position with respect to the patient's face. That is, the shroud module **20** acts as a carrier and bearing surface for the elbow module **70**. The shroud module **20** and elbow module **70** may connect with a friction fit, snap-fit, mechanical interlock, or other suitable attachment mechanism. However, other suitable arrangements for attaching the elbow module to the frame module are possible.

16

In FIGS. 27-30, the elbow module **70** may be rotatably attached to the shroud module **20** so that the elbow module **70** may be rotated relative to the shroud module **20** in use, e.g., 360° rotation.

The frame **1040** is structured to maintain the elbow **1070** in an operative position with respect to the patient's face. That is, the frame acts as a carrier and bearing surface for the elbow. The frame and elbow may connect with a friction fit, snap-fit, mechanical interlock, or other suitable attachment mechanism. However, other suitable arrangements for attaching the elbow to the frame are possible.

In the illustrated embodiment, the elbow **1070** includes a series of tangs **1075** adapted to releasably engage within the opening **1046** of the frame **1040**, e.g., with a snap-fit. The tangs **1075** hold the elbow in place (e.g., preferably a relatively airtight connection) and permit rotation or swiveling of the elbow with respect to the frame.

That is, the elbow is rotatably attached to the frame so that the elbow may be rotated relative to the frame in use, e.g., 360° rotation. This arrangement allows the elbow to assume different orientations in use, e.g., depending on patient preference. For example, the elbow may assume a first orientation so that the elbow extends generally downwardly from the mask to direct the air delivery tube under the patient's head in use. Alternatively, the elbow may be rotated and assume a second orientation so that the elbow extends upwardly from the mask to direct the air delivery tube over the patient's head in use. In an embodiment, the frame and elbow may be constructed of dissimilar materials to prevent or at least reduce squeak between the components in use.

The second end portion of the elbow may be provided to a swivel joint adapted to be connected to the air delivery tube. For example, FIGS. 27-30 illustrate a swivel joint **80** provided to the second end portion **74(2)** of elbow **70**. In the illustrated embodiment, the swivel joint **80** is provided to a short tube **82** (e.g., extendable and retractable tube) that interconnects the elbow with the air delivery tube. In an embodiment, the swivel joint **80** may be integrally formed in one piece with the short tube **82**.

4.2 AAV

The elbow **1070** includes a slot **1081** to receive an anti-asphyxia valve (AAV), a port **1079** that is selectively closed by a flap portion of the AAV (depending on the presence of pressurized gas), and structure for attaching the AAV, e.g., with a snap-fit.

FIGS. 27-30 illustrate an exemplary AAV **85** including a flap portion **86** to selectively close port **79** in elbow **70**. In this embodiment, a clip portion **88** is provided to the flap portion **86** for attaching the AAV **85** to the elbow **70**. In the illustrated embodiment, the flap portion **86** and the clip portion **88** are co-molded with one another to form a one-piece, integrated component. However, the flap portion **86** and clip portion **88** may be secured to one another in other suitable manners, e.g., mechanical interlock.

In an embodiment, the flap portion **86** may be constructed of a relatively soft elastomeric material (e.g., silicone) and the clip portion **88** may be constructed of a more rigid material (e.g., rigid plastic) for interfacing with the elbow **70**.

The clip portion **88** of the AAV **85** includes structure for removably interlocking with the elbow **70**, e.g., with a snap-fit. For example, the clip portion **88** may include tabs structured to interlock with respective recesses/protrusions provided to the elbow.

FIGS. 35-1 and 35-2 illustrate an elbow **270** including a port **279** that is selectively closed by a flap portion **286** of the AAV **285** (depending on the presence of pressurized gas).

17

Also, FIGS. 37-1 to 37-3 illustrate elbow 370 including a port 379 and a slot 381 to retain the AAV.

Alternative embodiments of the AAV are disclosed in PCT Application No. PCT/AU2006/000031, which is incorporated herein by reference in its entirety.

4.3 Large Diameter End Portion

As shown in FIGS. 27-30, the first end portion 74(1) of the elbow 70 may provide a relatively large diameter which allows the potential for cleaner/smooth lines thereby contributing to the overall mask aesthetic and reduced obtrusiveness. In addition, the relatively large diameter elbow offers the potential for the patient's nose to protrude into the elbow cavity thereby permitting the mask to be brought closer to the patient's face (i.e., reduced obtrusiveness), less moment since center of gravity of mask is closer to the patient's face, and/or improved line of sight.

5. Modular Design

The mask system provides a modular design that allows different styles and/or sizes of the frame (also referred to as a frame module), shroud (also referred to as a shroud module), cushion (also referred to as a cushion module), and/or elbow (also referred to as an elbow module) to be interchanged or mixed and matched with one another to provide a more customized mask system for the patient. In addition, such design allows selected modules to be easily replaced, e.g., treatment requirements change, worn out or damaged, etc.

In an embodiment, the mask system may be provided with a number of different cushions, e.g., each having cushions of different styles and/or sizes (e.g., depending on patient preference and/or fit). For example, the non-face contacting side of each cushion may include a common or universal configuration for interfacing with the frame, and the face-contacting side of the cushion may include different styles and/or sizes. This provides a modular arrangement that allows the frame to be selectively (e.g., and removably) coupled to one of multiple cushion. For example, the different cushions may include different size cushions (e.g., small, medium, and large) and may include a different cushion structures.

In an embodiment, the mask system may be provided with different shrouds, e.g., each shroud having a different style and/or size (e.g., shroud with different arrangement/style of headgear connectors, shroud with forehead support, different headgear vectors, etc).

In an embodiment, the mask system may be provided with different frames, e.g., each frame having a different style and/or size (e.g., frame with different vent arrangement, small, medium, and large size frame, etc).

In an embodiment, the mask system may be provided with a number of different elbows, e.g., each having a vent arrangement, AAV (in the case of an oro-nasal mask), and/or elbow of different styles and/or sizes. In the illustrated embodiment of FIGS. 27-30, the vent arrangement 76 and AAV 85 are structured to be removably attachable to the elbow 70. This provides a modular arrangement that allows the elbow to be selectively and removably coupled to one of multiple vent arrangements and/or AAVs. This also allows the vent arrangement and AAV to be easily replaced, e.g., if damaged.

5.1 Shroud to Frame Connection

The shroud is mounted on the outer surface of the frame, e.g., preferably with a tight, conforming fit on the frame.

5.1.1 Upper Retaining Mechanism

In the illustrated embodiment of FIGS. 1-5, the shroud 1020 is connected to the frame 1040 by an upper retaining mechanism or interfacing structure 1048 located on the top end of the frame and shroud.

18

As shown in FIGS. 2 to 5, the upper retaining mechanism 1048 is in the form of two taper locks structured to secure the shroud 1020 on the frame 1040 and prevent unintentional disassembly particularly due to headgear forces. In this embodiment, opposing sides of the frame include a female slot 1055 adapted to receive a respective tang protrusion (which tapers along its length) on the underside of the shroud 1020. The tapered protrusion engages within a respective female slot, e.g., with a friction fit.

FIGS. 10 to 19-4 show another embodiment of a mask system 1110 which more clearly illustrates an embodiment of the taper lock. FIGS. 10 to 17 show various views of the frame 1140, shroud 1120, and elbow 1170 of the mask system 1110.

As best shown in FIGS. 11 to 13, opposing sides of the top end of the frame 1140 include a platform 1154 which provides a first female slot 1155(1). In addition, the space between the platform 1154 and the outer surface of the frame 1140 defines a second female slot 1155(2). As best shown in FIG. 17, opposing sides of the top end of the shroud 1120 include a tang protrusion 1156 on the underside of the shroud 1120. The tang protrusion 1156 includes a first tang 1156(1) and a second tang 1156(2) that extends generally transverse to the first tang 1156(1). As shown in FIGS. 18-1 and 18-2, each tang may taper along its length, i.e., thinner towards its free end.

FIGS. 18-1 and 18-2 and 19-1 to 19-4 sequentially illustrate attachment of the shroud 1120 to the frame 1140. As illustrated, the tangs 1156(1), 1156(2) of each tang protrusion 1156 are structured to engage with respective slots 1155(1), 1155(2), e.g., with a friction fit. As best shown in FIGS. 19-1 to 19-4, each slot 1155(2) includes lead-ins or guides 1157 that curve along their length (i.e., extend in vertical and horizontal direction) so as to guide the tang 1156(2) into the slot 1155(2) and aid assembly. FIGS. 18-2 and 19-4 show the tangs 1156(1), 1156(2) when fully inserted with respective slots 1155(1), 1155(2).

In an alternative embodiment, as shown in FIG. 20, the upper retaining mechanism may include a clip-type arrangement. As illustrated, opposing sides of the top end of the frame 1240 provide a shoulder 1255(1) and a tapered protrusion 1255(2). Opposing sides of the top end of the shroud 1220 include a first tang 1256(1) and a second tang 1256(2) on the underside of the shroud 1220. In use, each first tang 1256(1) is engaged with the respective shoulder 1255(1) and the second tang 1256(2) is engaged or clipped onto the tapered protrusion 1255(2), e.g., with a snap-fit.

5.1.2 Lower Retaining Mechanism

In an embodiment, the shroud may also be connected to the frame by a lower retaining mechanism located on the bottom end of the frame and shroud. For example, a retaining mechanism may be provided to the opening of the shroud which is structured to interlock or otherwise engage with the opening of the frame.

For example, as shown in FIGS. 14, 15, 17, and 21, the opening 1132 of the shroud 1120 may include structure adapted to engage the collar 1149 surrounding the frame opening 1146 with a snap-fit. As illustrated, the shroud 1120 includes snap fingers 1145(1) (e.g., three snap fingers) and sandwich tabs 1145(2) (e.g., three sandwich tabs) that extend from the opening 1132. The snap fingers and sandwich tabs are alternatively spaced about the opening.

In use, the snap fingers 1145(1) resiliently deflect (e.g., 0.5 mm deflection) and engage respective part-annular protrusions 1149(1) provided to the collar 1149 (e.g., see FIGS. 22 and 23) to provide an initial retention of the shroud 1120 to the frame 1140 (e.g., with allowable stresses), e.g., to facilitate assembly and disassembly. In addition, as the snap fingers

19

1145(1) engage respective protrusions **1149(1)**, the sandwich tabs **1145(2)** are received in respective recesses **1149(2)** provided to the end of the collar **1149** (e.g., see FIGS. **22** and **23**). When the elbow **1170** is engaged with the frame **1140** (e.g., see FIG. **23**), an annular protrusion **1171** on the elbow **1170** is positioned on an opposing side of the sandwich tabs **1145(2)** so that the sandwich tabs **1145(2)** are sandwiched between the collar **1149** and the elbow **1170**. Thus, the sandwich tabs utilize elbow retention forces to retain the shroud on the frame during use. The elbow **1170** has a distal shoulder **1173** adapted to extend under the edge of the frame **1140** to retain the elbow to the frame. The snap fingers **1145(1)** allow the shroud to connect to the frame independent of the elbow.

In an alternative embodiment, as shown in FIG. **24**, the shroud's lower section may be structured to clip to a single point below the collar. As illustrated, the lower end of the shroud **1320** includes a snap finger **1345** that is engaged or clipped onto a protrusion **1349(1)** spaced below the collar **1349** of the frame **1340**, e.g., with a snap-fit. In this embodiment, the protrusion **1349** extends from the cover enclosing auxiliary ports. This arrangement may facilitate molding of the collar on the frame, e.g., uniform thickness of the collar prevents molding distortions. In addition, removal of the protrusions **1149(1)**/recesses **1449(2)** from the collar may reduce the risk of leak.

5.1.3 Finger Grip

In an embodiment, the outer surface of the frame **1040** may include finger grips or recessed portions **1097**, which are positioned to be exposed under the shroud **1020**. The finger grips are adapted to allow the patient an improved ability to grip the frame and/or shroud which is particularly useful when disengaging the shroud from the frame.

5.1.4 Alternative Interfacing Structure

In an alternative embodiment, as shown in FIG. **27-30**, the shroud **20** includes an open construction that provides an annular or part annular retaining portion **22** structured to retain the frame **40** and the elbow **70**. As illustrated, the annular retaining portion **22** includes an interfacing structure **23** along an inner edge that is adapted to interface with or otherwise removably connect to an interfacing structure **48** along the outer perimeter of the frame **40** (e.g., see FIG. **28**). In the illustrated embodiment, the interfacing structure **23** is in the form of opposed flanges **23(1)** that are adapted to interlock with respective locking structures **48(1)** provided on opposing sides of the frame **40**. However, other suitable arrangements for attaching the frame **40** to the shroud **20** are possible, e.g., friction fit, snap-fit, mechanical interlock, or other suitable attachment mechanism.

For example, the frame **40** may be coupled to the shroud **20** in a manner that allows the frame **40** to be locked in different angular positions with respect to the shroud **20**, e.g., pivotally mounted.

5.1.5 Alternative Upper Headgear Connector

FIGS. **40-1** to **40-7** illustrate a frame and a clip-on upper headgear connector or rigidizer according to another embodiment of the present invention.

The frame **442** includes an opening **449** adapted to engage a frame shroud and/or elbow. Around and under the opening **449** is the u-shaped slot **402** for gas washout and auxiliary ports **443** on each side thereof.

In this embodiment, each upper side of the frame **442** includes a retaining member **433** and an upper intermediate portion of the frame **442** includes retaining grooves **435**, which are structured and arranged to retain an upper headgear connector or rigidizer **424**.

As best shown in FIGS. **40-6** and **40-7**, the upper headgear connector **424** includes a pair of elongated arms or rigidizers

20

426 coupled by a pair of wire members **428**. Each rigidizer **426** includes a slot **427** at its free end adapted to receive a respective headgear strap in use.

In use, the upper headgear connector **424** is adapted to clip onto the frame **442** (e.g., see FIGS. **40-1** and **40-2**). Specifically, intermediate portions of the wire members **428** are received in respective grooves **435** of the frame **442**, and end portions of the wire members **428** extend through respective retaining members **433** with the rigidizers **426** providing a shoulder to interlock with respective retaining members **433**. FIGS. **40-4** and **40-5** show an upper portion of a retaining member **433** to illustrate the groove **433(1)** adapted to receive a respective wire. As illustrated, the end of the groove **433(1)** includes tapered side walls **433(2)** and drops off towards a rear side **433(3)** to position the rigidizers **426** into interlocking engagement with the retaining member **433**.

FIGS. **41-1** to **41-12** illustrate an upper portion of a frame and a clip-on upper headgear connector or rigidizer according to another embodiment of the present invention.

As illustrated, the upper portion of the frame **542** includes a retaining member **533** on each side thereof and a retaining groove **535** along an intermediate portion thereof, which are structured and arranged to retain an upper headgear connector or rigidizer **524**.

As best shown in FIGS. **41-5** and **41-12**, the upper headgear connector **524** includes a pair of elongated arms or rigidizers **526** coupled by a connecting portion **528**. Each rigidizer **526** includes a slot **527** at its free end adapted to receive a respective headgear strap in use. In addition, the upper headgear connector **524** includes a clip structure **525** on each side of the connecting portion **528**.

In use, the upper headgear connector **524** is adapted to clip onto the frame **542** (e.g., see FIGS. **41-1** and **41-2**). Specifically, the connecting portion **528** is received in the groove **535** of the frame **542**, and the clip structures **525** releasably interlock with respective retaining members **533**. As best shown in FIGS. **41-3** and **41-4**, each retaining member **533** provides a cross-bar, and each clip structure **525** provides a v-shaped configuration that is adapted to resiliently deflect through the cross-bar and provide a shoulder to releasably interlock with the cross-bar.

FIGS. **42-1** to **42-7** illustrate an alternative embodiment for engaging the upper headgear connector with the frame. As illustrated, each retaining member **533** provides an open-ended cross-bar, and each clip structure **525** provides an elongated arm. In this embodiment, the cross-bar is structured to resiliently deflect to allow the clip structure **525** to extend through the cross-bar and releasably engage the cross-bar, e.g., with a friction fit. In addition, the upper headgear connector **524** of FIGS. **42-1** to **42-7** includes a c-shaped clip structure **529** adapted to interlock with a tab **549** provided to the frame **542** (see FIGS. **42-1** and **42-2**).

5.1.6 Grommet Attachment

FIGS. **44** and **45** illustrate an alternative mask arrangement in which the shroud is attached to the frame via a grommet.

For example, as shown in FIG. **44**, the frame **740** includes a grommet **745** (e.g., constructed of a rubber) and the shroud **720** includes an opening **725** adapted to receive the grommet **745** to secure the shroud **720** to the frame **740**. As illustrated, the shroud **720** includes elongated upper and lower arms **724**, **726** each with a slot **727** at its free end adapted to receive a respective headgear strap in use.

FIG. **45** illustrates an alternative shroud **820** which includes a single arm with a slot **827** at each end adapted to receive a respective headgear strap in use. In addition, the shroud **820** provides an elongated inner slot **825** adapted to receive the grommet **745** of the frame **740**. The elongated slot

21

825 allows the grommet **745** to be fixed in one of multiple positions along the length of the slot **825**, in contrast to the shroud **720** which provides a single fixed position. In an embodiment, the shroud **820** may be slidable with respect to the grommet **745** to allow an infinite number of positions with respect to the frame **740**.

In each embodiment, the grommet **745** (e.g., constructed of a rubber) fixes the shroud in position but the inherent flexibility of the grommet provides a flexible connection to decouple the shroud from the frame and allow a range of movement between the two components, e.g., like a ball joint or gimbal. Such arrangement helps with fitting and sealing of the mask to the patient's face. That is, the flexible connection allows the mask to selectively adjust and/or self-fit with the patient's face.

5.2 Cushion to Frame Connection

In FIGS. 1-8, the non-face contacting side of the cushion **1060** is connected to frame **1040** in a tongue and groove relationship. The tongue **1066** (see FIGS. 1C, 1D, and 8) of the cushion **1060** is inserted within a groove **1041** (see FIGS. 1C and 1D) provided along the perimeter of the frame **1040**. The tongue and groove relationship may also include a locking lip or sealing lip **1068** (see FIGS. 1C, 1D, and 8) on the cushion that is adapted to interlock with an undercut bead **1042** (see FIGS. 1C and 1D) within the frame groove to fixably retain the cushion to the frame.

In the illustrated embodiment, the cushion **1060** also includes one or more positioning features located around its circumference to assist with proper alignment of the cushion with the frame **1040**. As shown in FIG. 7, the cushion **1060** includes notches and/or protrusions (e.g., two notches **1067** and one protrusion **1069**) adapted to engage with complementary features in the frame, e.g., interlocking relationship.

5.2.1 Co-Molding Frame and Cushion

In an embodiment, as shown in FIGS. 27-30, the frame **40** and cushion **44** may be co-molded with one another to form a one-piece, integrated component. For example, the frame **40** may be molded of a first material adapted to interface with the shroud **20** and the cushion **44** may be co-molded onto the frame **40** of a second material adapted to interface with patient's face.

In such embodiment, the cushion **44** may be constructed of a relatively soft elastomeric material (e.g., silicone) for sealing and the frame **40** may be constructed of a more rigid material than the cushion **44** (e.g., polycarbonate, polypropylene) for interfacing with the frame.

Co-molding the frame **40** to the cushion **44** provides a chemical bond without necessarily forming a mechanical interlock. As a result, the connection includes no cracks, a gas tight seal, and clean interface. Moreover, such co-molded connection relaxes tolerances as the mold materials are sufficiently flexible to fill in any gaps at the interface between the frame **40** and the cushion **44**. Also, the co-molded frame/cushion provides a reduced part count (reduced cost) and facilitates assembly/disassembly to the shroud **20**.

In an alternative embodiment, as shown in FIG. 33, the frame **40** and cushion **44** may be integrally formed in one piece, e.g., of a silicone material. That is, the frame **40** may have the same shape and structure as described above, but be integrally molded of the same material, e.g., silicone.

In an embodiment, the integrally formed frame **40**/cushion **44** may be co-molded to the shroud **20**, e.g., constructed of polycarbonate or polypropylene. For example, the shroud **20** may be constructed of a relatively rigid material (e.g., polycarbonate or polypropylene) and the frame **40**/cushion **44** may be co-molded onto the shroud **20** of a relatively soft elastomeric material (e.g., silicone).

22

5.3 Vent Arrangement

In FIGS. 1, 1B, 1C, 1D, and 2-5, the vent arrangement **1076** is provided to the frame and includes a plurality of holes **1077** (e.g., 5-100 holes, e.g., 20-50 holes, or about 35 holes) oriented at an angle (e.g., 45°) on the outer surface of the frame so as ensure the exhausted air is directed away from the patient and preferably their bed partner when the patient is sleeping. As shown in FIGS. 1C and 1D, each hole **1077** may include a contour or taper along its length. However, it should be appreciated that the vent arrangement may include other suitable arrangements, e.g., different number of holes, hole arrangement, positioning on frame, vent provides part of interlocking structure with shroud, etc.

FIG. 35-1 illustrates a vent arrangement **276** provided to the frame **240** for gas washout. In the illustrated embodiment, the vent arrangement **276** is in the form of a vent insert (e.g., elastomeric vent insert) that is adapted to be removably supported within an outlet opening in the frame **240**. The vent insert may be similar those described in U.S. Pat. Nos. 6,561,190, 6,561,191, and 7,207,335, each of which is incorporated herein by reference in its entirety. However, it should be appreciated that the vent arrangement may have other suitable forms (e.g., vent holes in frame **40** (FIG. 28), etc.).

FIGS. 37-3, 39-2, and 39-4 illustrate a frame **340** that includes a u-shaped slot **302** that receives a u-shaped plug-type vent **305** for gas washout. As illustrated, the plug-type vent **305** wraps around and under the opening in the frame **340** for the elbow **370**. The plug-type vent **305** includes a plurality of tracks or grooves **307** on each side thereof. In use, the grooved plug-type vent **305** forms a seal with the slot **302** so that exhausted air can exit between the slot walls and the grooves **307** on the plug-type vent **305**. In an embodiment, the port caps **347** may be integrated or incorporated into the plug-type vent **305** (e.g., integrally formed in one piece). Further details of such a plug-type vent arrangement are provided in U.S. patent application Ser. No. 12/230,120, filed Aug. 22, 2008, which is incorporated herein by reference in its entirety. FIGS. 39-2 to 39-6 show the frame **340** with the grooved plug-type vent **305** removed so as to more clearly illustrate the u-shaped slot **302** and auxiliary ports **343** on each side thereof.

Also, it should be appreciated that the vent arrangement may be provided to the elbow. For example, as shown in FIGS. 27-30, the vent arrangement **76** is in the form of a vent insert that is adapted to be removably supported within an outlet opening in the elbow **70**. In an embodiment, the vent arrangement **76** includes a base adapted to be supported within the outlet opening, one or more grill components or media (e.g., filter, membrane, or other porous material) provided to the base and structured to diffuse vent flow, and a cover to maintain the grill components/media within the base. Only the cover **77** of the vent arrangement **76** is visible in FIGS. 27-30.

Exemplary embodiments of such a vent arrangement are disclosed in U.S. patent application Ser. No. 12/230,120, filed Aug. 22, 2008, which is incorporated herein by reference in its entirety.

However, it should be appreciated that the vent arrangement may include other suitable arrangements, e.g., vent insert with one or more vent holes.

Also, the elbow may provide an alternative venting arrangement to the vent insert. For example, as indicated in dashed lines in FIG. 30, the first end portion **74(1)** of the elbow **70** (e.g., along the interfacing structure **75**) may include one or more vent holes **276** for gas washout. The one or more holes **276** may be provided to a soft part (e.g., silicone seal as described below) and/or a hard part (e.g., polycarbonate, polypropylene) of the elbow. The holes **276** may extend

23

around the entire perimeter of the first end portion **74(1)** or may extend along one or more portions of the first end portion **74(1)**. It is noted that providing vent holes along the entire perimeter of the elbow may help to disperse the vent flow in use. However, other suitable hole arrangements, hole numbers, and/or hole shapes along the first end portion **74(1)** and/or other portions of the elbow are possible.

5.4 Ports

In FIGS. **1-5**, the base of the frame **1040** includes two ports **1043** positioned so that in use, oxygen or other breathable gas can be delivered close to the patient's nares or pressure monitoring equipment can be attached. The ports **1043** may also be used to attach additional medical equipment such as pressure or flow sensors. The ports may be selectively closable or sealable by a ports cap.

In an alternative embodiment, as shown in FIGS. **25** and **26**, the frame **1040** may include a side port **1043.1**, e.g., in addition to or as an alternative to the ports **1043**.

FIGS. **35-1** and **35-2** show a frame **240** that includes an auxiliary port or spigot **243** on an upper portion of the frame, e.g., for supplemental oxygen, measurement device, etc.

In FIGS. **37-1** to **37-3** and **39-1** to **39-6**, the frame **340** includes an auxiliary port or spigot **343** on each side thereof, e.g., for supplemental oxygen, measurement device, etc. Port caps **347** are provided to seal respective ports **343**.

6. Interface Seal

In an embodiment, a seal may be provided at the interface between the elbow and the shroud, at the interface between the frame and the shroud, and/or at the interface between the elbow and the frame. For example, a seal (e.g., elastomeric, ring-shaped seal) may be formed separately from the modules and attached at the interface (e.g., sandwiched between modules, adhesive, etc.). Alternatively, a seal may be co-molded with one or more of the modules. In an embodiment, a silicone lip seal may be provided to the frame to seal against the elbow, thereby reducing leak.

In another embodiment, as shown in FIG. **27-30**, the interfacing structure **75** of the elbow **70** may be constructed of a relatively soft, sealing material (e.g., silicone, which may be co-molded to the harder material of the elbow) that is structured to provide a seal at the interface between the elbow **70** and the shroud **20**. Also, the relatively soft interfacing structure **75** (e.g., silicone) provides a "soft" attachment to the relatively hard shroud **20** (e.g., polycarbonate, polypropylene) which may allow an interference type fit. As noted above, one or more vent holes may be provided to the softer interfacing structure and/or the harder elbow.

While the invention has been described in connection with what are presently considered to be the most practical and preferred embodiments, it is to be understood that the invention is not to be limited to the disclosed embodiments, but on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the invention. Also, the various embodiments described above may be implemented in conjunction with other embodiments, e.g., aspects of one embodiment may be combined with aspects of another embodiment to realize yet other embodiments. Further, each independent feature or component of any given assembly may constitute an additional embodiment. Furthermore, each individual component of any given assembly, one or more portions of an individual component from one or more embodiments may include one or more ornamental design features. In addition, while the invention has particular application to patients who suffer from OSA, it is to be appreciated that patients who suffer from other illnesses (e.g., congestive heart failure, diabetes, mor-

24

bid obesity, stroke, bariatric surgery, etc.) can derive benefit from the above teachings. Moreover, the above teachings have applicability with patients and non-patients alike in non-medical applications.

What is claimed is:

1. A mask system, comprising:

(i) a shroud module; wherein the shroud module includes headgear connectors adapted to removably attach to respective headgear straps of headgear; and

(ii) a cushion module, comprising:

a rigid or semi-rigid frame defining a breathing chamber; and

a cushion to form a seal with the patient's face in a nasal bridge region, a cheek region and a lower lip/chin region of the patient's face,

wherein the cushion is constructed of a first, relatively soft, elastomeric material and the frame is constructed of a second material that is more rigid than the cushion,

wherein the shroud module and the cushion module are configured to be removably and non-rotatably coupleable to one another; and

wherein the frame includes a protruding vent arrangement having a plurality of holes, wherein the shroud module includes a first opening to accommodate said protruding vent arrangement, and further wherein the shroud module includes a second opening positioned to align with a frame opening of the frame leading to the breathing chamber.

2. The mask system of claim 1 wherein the cushion comprises one or more folds in a lower lip/chin region of the cushion.

3. The mask system of claim 2, wherein a nasal bridge portion of the cushion includes one or more folds to provide in use a higher level of adaptability or flexibility to the nasal bridge region of the cushion module relative to another region of the cushion module;

and further wherein the one or more folds in the nasal bridge region has a relatively high degree of flexibility and the one or more folds in the lower lip/chin region has a relatively low degree of flexibility.

4. The mask system of claim 1, wherein a nasal bridge portion of the cushion includes one or more folds to provide in use a higher level of adaptability or flexibility to the nasal bridge region of the cushion module relative to another region of the cushion module;

and further wherein each of said one or more folds comprises adjacent first side walls interconnected by a second side wall.

5. The mask system of claim 1, wherein the frame includes a collar surrounding said frame opening, and wherein the shroud includes a retaining portion with a plurality of snap fingers structured to engage the collar with a snap-fit.

6. The mask system of claim 1, wherein the shroud module includes upper and lower headgear connectors on each side of the shroud module.

7. The mask system of claim 6, wherein each upper headgear connector includes a slot adapted to receive a respective headgear strap in use.

8. The mask system of claim 7, wherein each lower headgear connector is adapted to be removably interlocked with a headgear clip associated with a respective headgear strap.

9. The mask system of claim 6, wherein the upper headgear connectors and the lower headgear connectors define a fulcrum point or moment of pivoting that is positioned between the upper headgear connectors and the lower headgear connectors.

25

10. The mask system of claim 1, wherein the shroud module includes an annular or part annular cushion retaining portion structured to retain the cushion module.

11. The mask system of claim 1, further comprising an elbow module adapted to be connected to an air delivery tube that delivers breathable gas to the patient.

12. The mask system of claim 11, wherein the elbow module is provided to the shroud module.

13. The mask system of claim 11, wherein the elbow module comprises polycarbonate.

14. The mask system of claim 11, wherein the elbow module and the shroud module are directly connected with a mechanical interlock while allowing 360 degree rotation of the elbow module.

15. The mask system of claim 11, wherein the elbow module includes an anti-asphyxia valve and wherein the anti-asphyxia valve includes a flap portion adapted to selectively close a port provided in the elbow module.

16. The mask system of claim 1, wherein the cushion module includes at least first and second cushion modules adapted to be provided to the shroud module, said at least first and second cushion modules being different from one another in at least one aspect.

17. The mask system of claim 1 comprising a small cushion module, a medium cushion module and a large cushion module, wherein each of said small cushion module, said medium cushion module and said large cushion module is removably coupleable to the same shroud module.

18. The mask system of claim 1, wherein the shroud module and the frame comprise polycarbonate and the cushion comprises silicone.

19. The mask system of claim 1, wherein:

the headgear includes a pair of upper straps and a pair of lower straps, with the upper straps being removably attached to respective ones of the headgear connectors and the lower straps being connected to respective ones of the headgear connectors,

a free end of each of the upper straps and the lower straps includes a hook tab structured to engage a remainder of the respective upper strap and respective lower strap to secure the upper and lower straps in place in a length adjustable manner,

the upper straps split to form a pair of top straps and a pair of rear straps, the top straps being connected together by a buckle and configured to pass over the top of the patient's head in use, the rear straps being adapted to pass behind the patient's head in use, and

a free end of each of the top straps has a hook tab threaded through the buckle to engage a remainder of the respective top strap to secure the top straps in place relative to the buckle in a length adjustable manner.

20. The mask system of claim 19, wherein the upper straps provide padding to the respective headgear connectors of the shroud module on the patient's face in use.

21. The mask system of claim 19, wherein the rear straps and the top straps form a closed loop to encircle a rear portion of the patient's head when in use.

22. The mask system of claim 19, wherein the frame includes a frame opening leading to the breathing chamber, and wherein the front opening of the shroud module and the frame opening of the frame are aligned along a common longitudinal axis, and wherein the shroud module and the cushion module are removably snap-fit attached to one another by moving the shroud module and the cushion module towards one another along the longitudinal axis.

23. The mask system of claim 22, wherein the headgear connectors are configured and arranged to allow pivoting of

26

the cushion module, when attached with the shroud module, about a fulcrum point or moment of pivoting that is positioned between the upper connectors and the lower connectors.

24. The mask system of claim 23, wherein the frame is rigid.

25. The mask system of claim 19, wherein the frame is rigid.

26. The mask system of claim 1, wherein the second opening of the shroud module and the frame opening of the frame are aligned along a common longitudinal axis, and wherein the mask system further comprises a snap-fit arrangement to removably snap-fit attach the shroud module and the cushion module to one another by moving the shroud module and the cushion module towards one another along the longitudinal axis.

27. The mask system of claim 26, wherein the headgear connectors are configured and arranged to allow pivoting of the cushion module, when attached with the shroud module, about a fulcrum point or moment of pivoting that is positioned between the upper connectors and the lower connectors.

28. The mask system of claim 1, wherein:

the frame includes a collar surrounding said frame opening, and wherein the shroud includes a retaining portion with at least one snap finger structured to engage the collar with a snap-fit,

the shroud module includes upper and lower headgear connectors on each side of the shroud module,

each upper headgear connector includes a slot adapted to receive a respective headgear strap in use,

each lower headgear connector is adapted to be removably interlocked with a headgear clip associated with a respective headgear strap,

the mask assembly further comprises an elbow module adapted to be connected to an air delivery tube that delivers breathable gas to the patient, and

the elbow module is rotatably attached to the shroud module while allowing 360 degree rotation of the elbow module.

29. The mask system of claim 28, wherein each of the shroud module and the frame comprises polycarbonate, and the cushion comprises silicone.

30. The mask system of claim 28, wherein the frame is rigid.

31. The mask system of claim 1, wherein the frame is rigid.

32. A system for treating a patient with sleep disordered breathing, comprising:

the mask system of claim 1;

a flow generator to generate a supply of air at positive pressure to be delivered to the mask system; and an air delivery tube configured to deliver the supply of air from the flow generator to the mask system.

33. A mask system, comprising:

(i) a shroud module; wherein the shroud module includes headgear connectors adapted to removably attach to respective headgear straps of headgear; and

(ii) a cushion module, comprising:

a frame defining a breathing chamber; and

a cushion to form a seal with the patient's face in at least a nasal bridge region and a cheek region of the patient's face,

wherein the cushion is constructed of a first, relatively soft, elastomeric material and the frame is constructed of a second material that is more rigid than the cushion, and a nasal bridge portion of the cushion includes one or more folds to provide in use a higher level of

27

adaptability or flexibility to the nasal bridge region of the cushion module relative to another region of the cushion module;

wherein the shroud module and the cushion module are configured to be removably coupleable to one another, and

wherein the shroud module includes a front opening of substantially circular shape and a retaining portion extending rearwardly from the front opening, towards the frame, and structured to snap-fit with the cushion module.

34. The mask system of claim 33, further comprising an elbow module directly mechanically interlocked with the shroud module while allowing 360 degree rotation of the elbow module.

35. The mask system of claim 33, wherein the shroud module includes upper and lower headgear connectors on each side of the shroud module;

wherein each upper headgear connector includes a slot adapted to receive a respective headgear strap in use; and wherein each lower headgear connector is adapted to be removably interlocked with a headgear clip associated with a respective headgear strap.

36. The mask system of claim 33, further comprising an elbow module adapted to be connected to an air delivery tube that delivers breathable gas to the patient, wherein the shroud module is structured to directly retain and carry the elbow module.

37. The mask system of claim 33, wherein the frame includes a frame opening leading to the breathing chamber, and wherein the front opening of the shroud module and the frame opening of the frame are aligned along a common longitudinal axis, and wherein the shroud module and the cushion module are removably snap-fit attached to one another by moving the shroud module and the cushion module towards one another along the longitudinal axis.

38. The mask system of claim 37, wherein the headgear connectors are configured and arranged to allow pivoting of the cushion module, when attached with the shroud module, about a fulcrum point or moment of pivoting that is positioned between the upper connectors and the lower connectors.

39. The mask system of claim 38, wherein the frame is rigid.

40. The mask system of claim 33, wherein the frame is semi-rigid or rigid.

41. The mask system of claim 40, wherein the frame is rigid.

42. A system for treating a patient with sleep disordered breathing, comprising:

the mask system of claim 33;

a flow generator to generate a supply of air at positive pressure to be delivered to the mask system; and an air delivery tube configured to deliver the supply of air from the flow generator to the mask system.

43. A mask system for delivery of a supply of air at positive pressure to a patient's airway, the mask system comprising:

a cushion module comprising a frame defining a breathing chamber configured to receive the positive pressure air, and a cushion to form a seal with the patient's face in a nasal bridge region, a cheek region and a lower lip/chin region of the patient's face, wherein the cushion is constructed of a first, relatively soft, elastomeric material and the frame is constructed of a second material that is more rigid than the cushion, the frame including a wash-out vent, the frame including an opening;

headgear to maintain the mask system in a desired position on the patient's face, the headgear comprising a pair of

28

upper headgear straps each configured to extend above a respective one of the patient's ears in use and a pair of lower headgear straps each configured to extend below a respective one of the patient's ears in use, wherein a free end of each of the upper headgear straps and the lower headgear straps includes a hook tab structured to engage a remainder of the respective upper headgear strap and respective lower headgear strap to secure the upper and lower straps in place in a length adjustable manner, wherein the headgear includes a pair of top straps and a pair of rear straps, each said top strap being configured to extend from generally above a respective ear of the patient such that the top straps cross over the top of the patient's head in use, the rear straps being adapted to pass behind the patient's head in use, and wherein the rear straps and the top straps together at least partly form a closed loop to encircle a rear portion of the patient's head when in use;

a shroud module including headgear connectors adapted to removably attach to the headgear, wherein the headgear connectors include two upper connectors associated with the upper headgear straps, the shroud module having an opening of circular shape, and two lower connectors associated with the lower headgear straps, each said upper headgear connector including a slot or receiving hole adapted to receive one of the upper headgear straps, wherein the shroud module and the frame of the cushion module are configured to be removably snap-fit attached to one another in a non-rotatable manner by pushing the shroud module towards the frame along a longitudinal axis of both the opening of the frame and the opening of the shroud; and

an elbow rotatably attached to and carried by the shroud module or the frame of the cushion module, the elbow being configured to deliver the positive pressure air to the breathing chamber, the elbow including a swivel adapted to connect to an air delivery tube, the elbow including an anti-asphyxia valve (AAV) and a port that is selectively closed by a flap portion of the AAV.

44. The mask system of claim 43, wherein:

each upper headgear connector includes a laterally elongated arm and the slot or receiving hole is positioned at a free end of the arm,

each arm is contoured to extend along the patient's cheek, curving below the patient's field of vision or eyes, and then curves upwards at an angle relative to a horizontal axis in use,

the arms are at least semi-rigid to help prevent up and down movement of the arms relative to the face of the patient, the top straps are integral with one another,

the frame, the shroud module and the headgear are structured to control rotation of the mask system in the sagittal and coronal planes of the patient in use, without a forehead support, and

the elbow is rotatably snap-fit to the frame of the cushion module.

45. The mask system of claim 43, wherein:

each upper headgear connector includes a laterally extending arm and the slot or receiving hole is positioned at a free end of the arm,

the arms are at least semi-rigid to help prevent up and down movement of the arms relative to the face of the patient, the elbow is rotatably snap-fit to the frame of the cushion module,

the top straps are integral with one another, and the frame includes a co-molded ring-shaped lip seal to seal against the elbow when connected.

29

46. The mask system of claim 43, wherein:

the elbow is rotatably attached the shroud module,
the upper headgear straps provide padding to the respective
headgear connectors of the shroud on the patient's face
in use,

the frame includes a protruding vent arrangement having a
plurality of holes, wherein the shroud module includes a
first opening to accommodate said protruding vent
arrangement, further wherein the shroud module
includes a second opening to accommodate the elbow,

the frame includes an opening and the frame further
includes a collar surrounding said opening, and wherein
the shroud module includes a retaining portion with one
or more rearward extending snap fingers structured to
engage the collar with a snap-fit, and

the top straps are connected together with a buckle allow-
ing independent adjustment of each of the top straps.

47. The mask system of claim 43, wherein the mask system
is configured and arranged to pivot about a fulcrum point or
moment of pivoting that is positioned between the upper
connectors and the lower connectors.

48. The mask system of claim 43, wherein the frame is
semi-rigid or rigid.

49. The mask system of claim 48, wherein the frame is
rigid.

50. A system for treating a patient with sleep disordered
breathing, comprising:

the mask system of claim 43; and

a flow generator to generate a supply of air at positive
pressure to be delivered to the mask system, wherein
the air delivery tube is configured to deliver the supply of
air from the flow generator to the mask system.

51. A mask system for delivery of a supply of air at positive
pressure to a patient's airway, the mask system comprising:

a cushion module comprising a frame defining a breathing
chamber configured to receive the positive pressure air,
and a cushion to form a seal with the patient's face in a
nasal bridge region, a cheek region and a lower lip/chin
region of the patient's face, wherein the cushion is con-
structed of a first, relatively soft, elastomeric material
and the frame is constructed of a second material that is
more rigid than the cushion, the frame including a wash-
out vent;

headgear to maintain the mask system in a desired position
on the patient's face, the headgear comprising a pair of
upper headgear straps each configured to extend above a
respective one of the patient's ears in use and a pair of
lower headgear straps each configured to extend below a
respective one of the patient's ears in use, wherein a free
end of each of the upper headgear straps and the lower
headgear straps includes a hook tab structured to engage
a remainder of the respective upper headgear strap and
respective lower headgear strap to secure the upper and
lower straps in place in a length adjustable manner,
wherein the headgear includes a pair of top straps and a
pair of rear straps, each said top strap being configured to
extend from generally above a respective ear of the
patient such that the top straps cross over the top of the
patient's head in use, the rear straps being adapted to
pass behind the patient's head in use, and wherein the
rear straps and the top straps together at least partly form
a closed loop to encircle a rear portion of the patient's
head when in use;

a shroud module including headgear connectors adapted to
removably attach to the headgear, wherein the headgear
connectors include two upper connectors associated with
the upper headgear straps and two lower connectors

30

associated with the lower headgear straps, each said
upper headgear connector including a slot or receiving
hole adapted to receive one of the upper headgear straps,
wherein the shroud module and the frame of the cushion
module are configured to be removably snap-fit attached
to one another in a non-rotatable manner; and

an elbow rotatably attached to and carried by the shroud
module or the frame of the cushion module, the elbow
being configured to deliver the positive pressure air to
the breathing chamber, the elbow including a swivel
adapted to connect to an air delivery tube, the elbow
including an anti-asphyxia valve (AAV) and a port that is
selectively closed by a flap portion of the AAV;

the elbow is rotatably attached the shroud module,
the upper headgear straps provide padding to the respective
headgear connectors of the shroud on the patient's face
in use,

the frame includes a protruding vent arrangement having a
plurality of holes, wherein the shroud module includes a
first opening to accommodate said protruding vent
arrangement, further wherein the shroud module
includes a second opening to accommodate the elbow,
the frame includes a frame opening and the frame further
includes a collar surrounding said frame opening, and
wherein the shroud module includes a retaining portion
with one or more rearward extending snap fingers struc-
tured to engage the collar with a snap-fit, and
the top straps are connected together with a buckle allow-
ing independent adjustment of each of the top straps.

52. The mask system of claim 51, wherein the mask system
is adapted to pivot about a fulcrum point or moment of piv-
oting that is positioned between the upper connectors and the
lower connectors.

53. The mask system of claim 51, wherein the second
shroud opening and the frame opening are aligned along a
common longitudinal axis, and wherein the shroud and the
frame are removably snap-fit attached to one another by mov-
ing the shroud and the frame towards one another along the
longitudinal axis.

54. The mask system of claim 51, wherein the frame is
semi-rigid or rigid.

55. The mask system of claim 54, wherein the frame is
rigid.

56. A system for treating a patient with sleep disordered
breathing, comprising:

the mask system of claim 51; and

a flow generator to generate a supply of air at positive
pressure to be delivered to the mask system, wherein
the air delivery tube is configured to deliver the supply of
air from the flow generator to the mask system.

57. A mask system for treating a patient with sleep disor-
dered breathing with a supply of air at positive pressure,
comprising:

headgear including headgear straps;

a shroud module having a pair of upper headgear connec-
tors and a pair of lower headgear connectors adapted to
removably attach to the respective headgear straps of the
headgear, the shroud module having a front opening;

a rotatable elbow directly attached to the shroud; and
a cushion module, the cushion module comprising a frame
defining a breathing chamber, the frame having a frame
opening leading to the breathing chamber; and a cushion
to form a seal with the patient's face, wherein the cush-
ion comprises a first, relatively soft, elastomeric material
and the frame comprises a second material that is more
rigid than the cushion;

31

wherein:

the front opening of the shroud module and the frame opening of the frame are aligned along a common longitudinal axis, and wherein the shroud module and the cushion module are structured and arranged to be removably snap-fit attached to one another by moving the shroud module and the cushion module towards one another along the longitudinal axis, and

the shroud module includes a retaining portion positioned rearwardly of the front opening, towards the frame, and structured to snap fit with the cushion module.

58. The mask system of claim 57, wherein the shroud module and the cushion module are structured and arranged to be detached from one another by moving the shroud module and the cushion module away from one another along the longitudinal axis.

59. The mask system of claim 57, wherein the upper and lower headgear connectors are configured and arranged to allow pivoting of the cushion module, when attached with the shroud module, about a fulcrum point or moment of pivoting that is positioned between the upper headgear connectors and the lower headgear connectors.

60. The mask system of claim 57, wherein each upper headgear connector includes a slot adapted to receive a respective headgear strap in use; and

wherein each lower headgear connector is adapted to be removably interlocked with a headgear clip associated with a respective headgear strap.

61. The mask system of claim 57, wherein the elbow is adapted to be connected to an air delivery tube that delivers breathable gas to the patient.

62. The mask system of claim 57, wherein:

the headgear includes upper straps and lower straps,

a free end of each of the upper straps and the lower straps includes a hook tab structured to engage a remainder of the respective upper strap and respective lower strap to secure the upper and lower straps in place in a length adjustable manner,

the upper straps split to form a pair of top straps and a pair of rear straps, the top straps being connected together by a buckle and configured to pass over the top of the patient's head in use, the rear straps being adapted to pass behind the patient's head in use, and

a free end of each of the top straps has a hook tab threaded through the buckle to engage a remainder of the respective top strap to secure the top straps in place relative to the buckle in a length adjustable manner.

63. The mask system of claim 62, wherein the upper straps provide padding to the respective headgear connectors of the shroud module on the patient's face in use.

64. The mask system of claim 62, wherein the rear straps and the top straps form a closed loop to encircle a rear portion of the patient's head when in use.

65. The mask system of claim 57, wherein the frame includes a protruding vent arrangement having a plurality of gas washout holes, wherein the shroud module includes an upper opening to accommodate said protruding vent arrangement.

66. The mask system of claim 57, wherein the cushion comprises one or more folds in a lower lip/chin region of the cushion.

67. The mask system of claim 66, wherein a nasal bridge portion of the cushion includes one or more folds to provide in use a higher level of adaptability or flexibility to the nasal bridge region of the cushion module relative to another region of the cushion module;

32

and further wherein the one or more folds in the nasal bridge region has a relatively high degree of flexibility and the one or more folds in the lower lip/chin region has a relatively low degree of flexibility.

68. The mask system of claim 57, wherein a nasal bridge portion of the cushion includes one or more folds to provide in use a higher level of adaptability or flexibility to the nasal bridge region of the cushion module relative to another region of the cushion module;

and further wherein each of said one or more folds comprises adjacent first side walls interconnected by a second side wall.

69. The mask system of claim 57, wherein the frame includes a collar surrounding said frame opening, and wherein the retaining portion of the shroud includes a plurality of snap fingers structured to engage the collar with a snap-fit.

70. The mask system of claim 57, wherein the elbow includes an anti-asphyxia valve and wherein the anti-asphyxia valve includes a flap portion adapted to selectively close a port provided in the elbow.

71. The mask system of claim 57, wherein each of the shroud module and the frame comprises polycarbonate and the cushion comprises silicone.

72. The mask system of claim 57, wherein:

the shroud module and the cushion module are structured and arranged to be detached from one another by moving the shroud module and the cushion module away from one another along the longitudinal axis,

wherein each upper headgear connector includes a slot adapted to receive a respective headgear strap in use, and wherein each lower headgear connector is adapted to be removably interlocked with a headgear clip associated with a respective headgear strap,

the elbow is adapted to be connected to an air delivery tube that delivers breathable gas to the patient,

the headgear includes upper straps and lower straps, a free end of each of the upper straps and the lower straps includes a hook tab structured to engage a remainder of the respective upper strap and respective lower strap to secure the upper and lower straps in place in a length adjustable manner, the upper straps split to form a pair of top straps and a pair of rear straps, the top straps being connected together by a buckle and configured to pass over the top of the patient's head in use, the rear straps being adapted to pass behind the patient's head in use, and a free end of each of the top straps has a hook tab threaded through the buckle to engage a remainder of the respective top strap to secure the top straps in place relative to the buckle in a length adjustable manner,

the upper straps provide padding to the respective headgear connectors of the shroud module on the patient's face in use,

the rear straps and the top straps form a closed loop to encircle a rear portion of the patient's head when in use, the frame includes a protruding vent arrangement having a plurality of gas washout holes, wherein the shroud module includes an upper opening to accommodate said protruding vent arrangement,

the cushion comprises one or more folds in a lower lip/chin region of the cushion,

a nasal bridge portion of the cushion includes one or more folds to provide in use a higher level of adaptability or flexibility to the nasal bridge region of the cushion module relative to another region of the cushion module,

the frame includes a collar surrounding said frame opening, and wherein the retaining portion of the shroud includes a plurality of snap fingers structured to engage the collar with a snap-fit,

each of the shroud module and the frame comprises polycarbonate and the cushion comprises silicone.

73. The mask system of claim 72, wherein the upper and lower headgear connectors are configured and arranged to allow pivoting of the cushion module, when attached with the shroud module, about a fulcrum point or moment of pivoting that is positioned between the upper headgear connectors and the lower headgear connectors.

74. The mask system of claim 72, wherein the elbow includes an anti-asphyxia valve and wherein the anti-asphyxia valve includes a flap portion adapted to selectively close a port provided in the elbow.

75. The mask system of claim 72, wherein the frame is semi-rigid or rigid.

76. The mask system of claim 75, wherein the frame is rigid.

77. The mask system of claim 57, wherein the frame is semi-rigid or rigid.

78. The mask system of claim 77, wherein the frame is rigid.

79. A system for treating a patient with sleep disordered breathing, comprising:

the mask system of claim 57;

a flow generator to generate a supply of air at positive pressure to be delivered to the mask system; and

an air delivery tube configured to deliver the supply of air from the flow generator to the mask system.

* * * * *